

Nylon Sleeving



- High abrasion resistance
- Resistant to water, oil and hydraulic fluids
- Useful for bundling 2 or more hose
- MSHA approved flame resistant
- Temperature range: -40°C to 125°C (-40°F to 250°F)

Part Number	Flat Width	Round ID	Standard Pack
	in	in	ft
NS-077	1.38	0.77	300
NS-090	1.59	0.90	300
NS-100	1.66	1.00	300
NS-114	1.81	1.14	300
NS-122	2.05	1.22	300
NS-138	2.36	1.38	300
NS-159	2.64	1.59	300
NS-181	2.87	1.81	300
NS-219	3.58	2.19	300
NS-238	3.94	2.38	300
NS-263	4.21	2.63	300
NS-296	4.96	2.96	300
NS-366	5.81	3.66	300

Nylon Sleeve - Velcro



- For easy installation and simple retrofits

Part Number	Flat Width	Round ID	Standard Pack
	in	in	ft
NSV-200B	7.75	2.00	150
NSV-300B	10.90	3.00	150
NSV-400B	14.00	4.00	150
NSV-500B	17.25	5.00	150
NSV-600B	20.38	6.00	150
NSV-700B	23.50	7.00	150
NSV-800B	26.62	8.00	150

Polyurethane Sleeving



- Ideal for abrasion protection or bundling hose assemblies
- MSHA approved
- Temperature range: -40°C to 125°C (-40°F to 250°F)

Black Part Number	Yellow Part Number	Wall Thickness	Nominal ID B	Standard Package
		in	in	ft
PS-0625B	PS-0625Y	0.045	0.625	30
PS-0750B	PS-0750Y	0.045	0.750	30
PS-0875B	PS-0875Y	0.045	0.875	30
PS-1000B	PS-1000Y	0.045	1.000	30
PS-1125B	PS-1125Y	0.045	1.125	30
PS-1250B	PS-1250Y	0.045	1.250	30
PS-1375B	PS-1375Y	0.045	1.375	30
PS-1500B	PS-1500Y	0.045	1.500	30
PS-1625B	PS-1625Y	0.045	1.625	30
PS-1750B	PS-1750Y	0.045	1.750	30
PS-2000B		0.060	2.000	30
	PS-2125Y	0.060	2.125	30

7

Fire Sleeving



- 500°F (260°C) continuous
- 2000°F (1090°C) for 15-20 minutes
- 3000°F (1650°C) for 15-20 seconds
- Fibreglass sleeve coated with a thick iron oxide red silicon rubber
- Protects hoses from molten metal splash, radiant heat, abrasion, chemical, vibration and electricity

Part Number	Nominal ID B	Standard Package
	in	ft
FS-050	0.50	50
FS-063	0.63	50
FS-075	0.75	50
FS-088	0.88	50
FS-100	1.00	50
FS-113	1.13	50
FS-138	1.38	50
FS-163	1.63	50
FS-175	1.75	50
FS-200	2.00	50

Fire Sleeve Tape
 PST-16 1" WIDE
 PST-24 1½" WIDE

BECAUSE WE CONTINUALLY EXAMINE WAYS TO IMPROVE OUR PRODUCTS, WE RESERVE THE RIGHT TO ALTER SPECIFICATIONS WITHOUT NOTICE.