# **DEF - Hose & Fittings**

### **DF10** DIESEL EXHAUST FLUID (DEF)

FORSAFLEX DF10-075 3/4"

ORSAFLEX DF20-100 1"

Tube: Reinforcement: Cover: Temperature: Application:	Polyurethane Synthetic fiber Black specially blended TPR -20°C to +65°C (-4°F to +149°F) DF10 Dispensing Hose is specifically designed to convey the high-purity, aqueous urea solution (DEF). <b>Not for submersion applications.</b>
Branding:	FORSAFLEX DF10-075 3/4" DEF HOSE 210 PSI MAX ISO-22241

Part Number		→(( 0	)← D	₩ Max WP		Standard Pack
	in	in	mm	psi (20°C / 70°F)	lbs/ft	
DF10-050	1⁄2	0.75	19.1	210	0.20	200' - Coil
DF10-075	3⁄4	1.03	26.2	210	0.24	200' - Coil
DF10-100	1	1.33	33.8	210	0.42	200' - Coil

### DF20 DIESEL EXHAUST FLUID (DEF)

Tube: Reinforcement: Cover: Temperature: Application:	Polyurethane Synthetic fiber with steel helix Blue specially blended TPR -20°C to +65°C (-4°F to +149°F) Truck delivery and tank unloading can be used in both suction and discharge applications. <b>Not for submersion applications.</b>
Branding:	FORSAFLEX DF20-100 1" DEF SUCTION HOSE 175 PSI MAX WP ISO-22241

Part Number	→⊖→ ID in	→( O in	D D mm	← Max WP psi (20°C / 70°F)	Weight Ibs/ft	Standard Pack
DF20-100	1	1.42	36.1	175	0.45	200′ - Coil
DF20-125	1-¼	1.66	42.2	175	0.52	200' - Coil
DF20-150	1-1⁄2	2.01	51.0	175	0.77	200' - Coil
DF20-200	2	2.51	63.8	175	1.075	200' - Coil

BECAUSE WE CONTINUALLY EXAMINE WAYS TO IMPROVE OUR PRODUCTS, WE RESERVE THE RIGHT TO ALTER SPECIFICATIONS WITHOUT NOTICE.

FORSAFLEX

## **DEF - Hose & Fittings** DEF FITTINGS - 316 STAINLESS STEEL



MALE NPT SOLID STAINLESS		
Hose x Thread Size	Part Number	
½″ x ½″	DF08-08MP-SS	
<sup>3</sup> /4" x <sup>3</sup> /4"	DF12-12MP-SS	

2″ x 2″	DF32-32MP-SS
1 ½″ x 1 ½″	DF24-24MP-SS
1 ¼″ x 1 ¼″	DF20-20MP-SS
1″ x 1″	DF16-16MP-SS
³⁄4″ x ³⁄4″	DF12-12MP-SS
½″ x ½″	DF08-08MP-SS



### MALE NPT SWIVEL STAINLESS

Hose x Thread Size	Part Number
½″ x ½″	DF08-08MPX-SS
<sup>3</sup> ⁄4″ X <sup>3</sup> ⁄4″	DF12-12MPX-SS
1″ x 1″	DF16-16MPX-SS



Hose x Thread Size	Part Number
<sup>3</sup> ⁄4″ X <sup>3</sup> ⁄4″	DF12-12MBSPPX-SS
1″ x 1″	DF16-16MBSPPX-SS



FEMALE BSPP FLAT FACE
SWIVEL STAINLESS

Hose x Thread Size	Part Number
<sup>3</sup> ⁄4″ X <sup>3</sup> ⁄4″	DF12-12FBSPPX-SS
1″ x 1″	DF16-16FBSPPX-SS



#### DEF STAINLESS MALE CAMLOCK

Fitting Size Part No	DEF STAINLESS WALL CAWLOCK		
	).		
1-1/2" DFSS-E1	50		
2" DFSS-E20	00		
3" DFSS-E30	00		



#### DEF STAINLESS FEMALE CAMLOCK

Fitting Size	Part No.
1-1⁄2"	DFSS-C150
2″	DFSS-C200
3″	DFSS-C300



DEF FERRULE	
Size	Part Number
1⁄2″	170-08
3⁄4″	170-12
1″	170-16
1-¼″	DEF-125F
1-1⁄2″	DEF-150F
2″	DEF-200F

- ------

BECAUSE WE CONTINUALLY EXAMINE WAYS TO IMPROVE OUR PRODUCTS, WE RESERVE THE RIGHT TO ALTER SPECIFICATIONS WITHOUT NOTICE.