


## PGH THE PERFECT GARDEN HOSE®



<b>Tube:</b>	Clear TPE
<b>Reinforcement:</b>	Polypropylene 2 Helix Design, Color Blue 2 ply spiral polyester fiber
<b>Cover:</b>	TPE with color Blue/Green
<b>Temperature:</b>	-29°C to +70°C (-20°F to +158°F)
<b>Weight:</b>	0.13 lbs/ft

**Application:** The Perfect Garden Hose's unique double helix construction makes this a very flexible and only "unkinkable" garden hose. The Perfect Garden Hose is 35%-50% lighter than the average garden hose and maintains flexibility in cold temperatures. It is assembled with heavy duty brass fittings. All of these features make The Perfect Garden Hose ideal for residential and light commercial users. PGH hose is suited for washing cars, RVs, or boats and also wash-down use in industrial plants, horse barns, and landscape applications.

## PGH THE PERFECT GARDEN HOSE® ASSEMBLIES

Part Number	Color	Hose Size	 Max WP	Fitting A	Fitting B	Length	Attaching Method
			psi @ 20°C / 70°F			ft	
PGH-25-BL	Blue	5/8	100	M-GHT	F-GHT	25	Crimp
PGH-50-BL	Blue	5/8	100	M-GHT	F-GHT	50	Crimp
PGH-100-BL	Blue	5/8	100	M-GHT	F-GHT	100	Crimp
PGH-50-GN	Green	5/8	100	M-GHT	F-GHT	50	Crimp
PGH-100-GN	Green	5/8	100	M-GHT	F-GHT	100	Crimp
PGH-50-RD	Red	5/8	100	M-GHT	F-GHT	50	Crimp

BECAUSE WE CONTINUALLY EXAMINE WAYS TO IMPROVE OUR PRODUCTS, WE RESERVE THE RIGHT TO ALTER SPECIFICATIONS WITHOUT NOTICE.

# Water Discharge Hose

## GH10 GOLF COURSE HOSE



- Tube:** Black PVC
- Reinforcement:** Synthetic fiber
- Cover:** Smooth transparent green PVC compound
- Temperature:** -4°C to +65°C (+25°F to +150°F)
- Application:** An all-purpose heavy duty PVC hose that is ideal for golf courses and parks.

Part Number	ID		OD		Max WP	Weight	Standard Pack
	in	mm	in	mm	psi @ 20°C / 70°F	lbs/ft	
GH10-075	3/4	19.0	1.03	26.0	125	0.22	300' - Coil
GH10-100	1	25.4	1.30	32.9	125	0.30	50/100' - Coil

## GH10 GOLF COURSE ASSEMBLIES



GHT M x F



NPSM M x F

Part Number	Hose Size	Brass Fitting A	Brass Fitting B	Length	Attaching Method
				ft	
GH10-075GHT50	3/4	M-GHT	F-GHT	50	Crimp
GH10-075GHT100	3/4	M-GHT	F-GHT	100	Crimp
GH10-100GHT50	1	M-NPSM	F-NPSM	50	Crimp
GH10-100GHT100	1	M-NPSM	F-NPSM	100	Crimp

Other lengths and fitting combinations are available.





BECAUSE WE CONTINUALLY EXAMINE WAYS TO IMPROVE OUR PRODUCTS, WE RESERVE THE RIGHT TO ALTER SPECIFICATIONS WITHOUT NOTICE.



## WD10 BLUE PVC LAYFLAT

**Tube:** Blue PVC  
**Reinforcement:** Synthetic fiber  
**Cover:** Blue PVC  
**Temperature:** -10°C to +55°C (15°F to +130°F)  
**Application:** A light duty layflat hose for portable pump and irrigation use.

**Branding:** FORSAFLEX WD10-200 65 PSI MAX WP

Part Number						Standard Pack
	in	in	mm	psi	lbs/ft	
WD10-100	1	1.11	28.1	100	0.11	300' - Coil
WD10-125	1-¼	1.36	34.5	85	0.12	300' - Coil
WD10-150	1-½	1.61	40.9	70	0.14	300' - Coil
WD10-200	2	2.11	53.6	65	0.20	300' - Coil
WD10-250	2-½	2.62	66.5	60	0.27	300' - Coil
WD10-300	3	3.13	79.5	60	0.34	300' - Coil
WD10-400	4	4.13	104.9	60	0.48	300' - Coil
WD10-600	6	6.14	155.9	40	0.77	300' - Coil
WD10-800	8	8.15	207.0	35	1.21	300' - Coil
WD10-1000	10	10.12	257.0	35	1.81	100' - Coil
WD10-1200	12	12.13	308.1	30	1.95	100' - Coil

## WD10 BLUE PVC LAYFLAT ASSEMBLIES



Camlock C x E



NPSH M x F

Part Number	Hose Size	Fitting A	Fitting B	Length	Attaching Method
				ft	
WD10-150CE50	1-½	C	E	50	Band Clamps
WD10-200CE50	2	C	E	50	Band Clamps
WD10-300CE50	3	C	E	50	Band Clamps
WD10-400CE50	4	C	E	50	Band Clamps
WD10-600CE50	6	C	E	50	Band Clamps
WD10-150MF50	1-½	M-NPSH	F-NPSH	50	Band Clamps
WD10-200MF50	2	M-NPSH	F-NPSH	50	Band Clamps
WD10-300MF50	3	M-NPSH	F-NPSH	50	Band Clamps
WD10-400MF50	4	M-NPSH	F-NPSH	50	Band Clamps
WD10-600MF50	6	M-NPSH	F-NPSH	50	Band Clamps

BECAUSE WE CONTINUALLY EXAMINE WAYS TO IMPROVE OUR PRODUCTS, WE RESERVE THE RIGHT TO ALTER SPECIFICATIONS WITHOUT NOTICE.




# Water Discharge Hose



## WD12 GRAY PVC LAYFLAT

**Tube:** Gray PVC  
**Reinforcement:** Synthetic fiber  
**Cover:** Gray PVC  
**Temperature:** -10°C to +55°C (15°F to +130°F)  
**Application:** A medium duty layflat hose for portable pump and irrigation use.

**Branding:** FORSAFLEX WD12-200 120 PSI MAX WP

Part Number						Standard Pack
	ID	OD		Max WP	Weight	
	in	in	mm	psi	lbs/ft	
WD12-150	1-½	1.63	41.5	75	0.19	300' - Coil
WD12-200	2	2.13	54.2	120	0.26	300' - Coil
WD12-300	3	3.23	82.0	110	0.44	300' - Coil
WD12-400	4	4.39	111.6	110	0.73	300' - Coil
WD12-600	6	6.20	157.4	35	1.14	300' - Coil

## WD12 GRAY PVC LAYFLAT ASSEMBLIES



Camlock C x E



NPSH M x F

Part Number	Hose Size	Fitting A	Fitting B	Length	Attaching Method
				ft	
WD12-150CE50	1-½	C	E	50	Band Clamps
WD12-200CE50	2	C	E	50	Band Clamps
WD12-300CE50	3	C	E	50	Band Clamps
WD12-400CE50	4	C	E	50	Band Clamps
WD12-600CE50	6	C	E	50	Band Clamps
WD12-150MF50	1-½	M-NPSH	F-NPSH	50	Band Clamps
WD12-200MF50	2	M-NPSH	F-NPSH	50	Band Clamps
WD12-300MF50	3	M-NPSH	F-NPSH	50	Band Clamps
WD12-400MF50	4	M-NPSH	F-NPSH	50	Band Clamps
WD12-600MF50	6	M-NPSH	F-NPSH	50	Band Clamps

Other lengths and fitting combinations are available.





BECAUSE WE CONTINUALLY EXAMINE WAYS TO IMPROVE OUR PRODUCTS, WE RESERVE THE RIGHT TO ALTER SPECIFICATIONS WITHOUT NOTICE.



## WD13 RED/BROWN PVC LAYFLAT

**Tube:** Brown PVC  
**Reinforcement:** Synthetic fiber  
**Cover:** Brown PVC  
**Temperature:** -10°C to +55°C (5°F to +130°F)  
**Application:** This hose is a more rugged version of our blue PVC layflat hose, designed for use where higher working pressures are required. Common applications are rental, construction, mining, agricultural and marine service.

**Branding:** FORSAFLEX WD13-200 2" 115 PSI MAX WP

Part Number						Standard Pack
	ID	OD		Max WP	Weight	
	in	in	mm	psi	lbs/ft	
WD13-150	1-½	1.63	41.4	120	0.15	300' - Coil
WD13-200	2	2.14	54.4	115	0.23	300' - Coil
WD13-250	2-½	2.63	66.8	100	0.30	300' - Coil
WD13-300	3	3.13	79.5	100	0.36	300' - Coil
WD13-400	4	4.13	104.9	90	0.50	300' - Coil
WD13-600	6	6.15	156.2	75	0.80	300' - Coil
WD13-800	8	8.17	207.5	75	1.31	300' - Coil

## WD13 RED/BROWN PVC LAYFLAT ASSEMBLIES



Camlock C x E

NPSH M x F

Part Number	Hose Size	Fitting A	Fitting B	Length	Attaching Method
				ft	
WD13-150CE50	1-½	C	E	50	Band Clamps
WD13-200CE50	2	C	E	50	Band Clamps
WD13-300CE50	3	C	E	50	Band Clamps
WD13-400CE50	4	C	E	50	Band Clamps
WD13-600CE50	6	C	E	50	Band Clamps
WD13-150MF50	1-½	M-NPSH	F-NPSH	50	Band Clamps
WD13-200MF50	2	M-NPSH	F-NPSH	50	Band Clamps
WD13-300MF50	3	M-NPSH	F-NPSH	50	Band Clamps
WD13-400MF50	4	M-NPSH	F-NPSH	50	Band Clamps
WD13-600MF50	6	M-NPSH	F-NPSH	50	Band Clamps

Other lengths and fitting combinations are available.

BECAUSE WE CONTINUALLY EXAMINE WAYS TO IMPROVE OUR PRODUCTS, WE RESERVE THE RIGHT TO ALTER SPECIFICATIONS WITHOUT NOTICE.

# Water Discharge Hose



## WD14 HD RED/BROWN PVC LAYFLAT

**Tube:** Brown PVC  
**Reinforcement:** Synthetic fiber  
**Cover:** Brown PVC  
**Temperature:** -10°C to +55°C (5°F to +130°F)  
**Application:** This hose is a more rugged version of our blue PVC layflat hose, designed for use where higher working pressures are required. Common applications are rental, construction, mining, agricultural and marine service.

**Branding:** FORSAFLEX WD14-200 2" 150 PSI MAX WP

Part Number						Standard Pack
	ID	OD		Max WP	Weight	
	in	in	mm	psi	lbs/ft	
WD14-150	1-½	1.65	41.9	150	0.20	300' - Coil
WD14-200	2	2.16	54.9	150	0.28	300' - Coil
WD14-250	2-½	2.67	67.8	150	0.44	300' - Coil
WD14-300	3	3.19	81.0	150	0.54	300' - Coil
WD14-400	4	4.20	106.7	125	0.67	300' - Coil
WD14-600	6	6.21	157.7	115	1.25	300' - Coil
WD14-800	8	8.22	208.9	70	1.48	300' - Coil

## WD14 HD RED/BROWN PVC LAYFLAT ASSEMBLIES



Camlock C x E



NPSH M x F

Part Number	Hose Size	Fitting A	Fitting B	Length	Attaching Method
				ft	
WD14-150CE50	1-½	C	E	50	Band Clamps
WD14-200CE50	2	C	E	50	Band Clamps
WD14-300CE50	3	C	E	50	Band Clamps
WD14-400CE50	4	C	E	50	Band Clamps
WD14-600CE50	6	C	E	50	Band Clamps
WD14-150MF50	1-½	M-NPSH	F-NPSH	50	Band Clamps
WD14-200MF50	2	M-NPSH	F-NPSH	50	Band Clamps
WD14-300MF50	3	M-NPSH	F-NPSH	50	Band Clamps
WD14-400MF50	4	M-NPSH	F-NPSH	50	Band Clamps
WD14-600MF50	6	M-NPSH	F-NPSH	50	Band Clamps

Other lengths and fitting combinations are available.

BECAUSE WE CONTINUALLY EXAMINE WAYS TO IMPROVE OUR PRODUCTS, WE RESERVE THE RIGHT TO ALTER SPECIFICATIONS WITHOUT NOTICE.

# Water Discharge Hose



## WD15 HIVIZ GREEN PVC LAYFLAT (PHTHALATE FREE) 150

**Tube:** Green PVC  
**Reinforcement:** Synthetic fiber  
**Cover:** HIVIZ Green PVC  
**Temperature:** -10°C to +55°C (5°F to +130°F)  
**Application:** This hose is a more rugged version of our blue PVC layflat hose, designed for use where higher working pressures are required. Common applications are rental, construction, mining, agricultural and marine service.

**Branding:** FORSAFLEX WD15-200 2" 150 PSI MAX WP

Part Number	ID		OD		Max WP	Weight	Standard Pack
	in	mm	in	mm	psi	lbs/ft	
WD15-200	2	50.8	2.14	54.4	150	0.23	300' - Coil
WD15-300	3	76.2	3.13	79.5	150	0.36	300' - Coil

## WD15 HIVIZ GREEN PVC LAYFLAT ASSEMBLIES



Camlock C x E



NPSH M x F

Part Number	Hose Size	Fitting A	Fitting B	Length	Attaching Method
				ft	
WD15-200CE50	2	C	E	50	Band Clamps
WD15-300CE50	3	C	E	50	Band Clamps
WD15-200MF50	2	M-NPSH	F-NPSH	50	Band Clamps
WD15-300MF50	3	M-NPSH	F-NPSH	50	Band Clamps

Other lengths and fitting combinations are available.

BECAUSE WE CONTINUALLY EXAMINE WAYS TO IMPROVE OUR PRODUCTS, WE RESERVE THE RIGHT TO ALTER SPECIFICATIONS WITHOUT NOTICE.

# Water Discharge Hose

## WD20 DURAFLOW (OROFLEX STYLE)



**Tube:** Black PVC/Nitrile  
**Reinforcement:** Circular woven synthetic fiber  
**Cover:** Black ribbed abrasion and oil resistant nitrile/PVC rubber  
**Temperature:** -30°C to +80°C (-22°F to +176°F)  
**Application:** This is a lightweight high pressure, extremely strong hose for plant washdown, as well as high pressure general water discharge for construction and rental companies.

Water Discharge Hose

Part Number	Cover	ID		OD		Max WP psi	Weight lbs/ft	Standard Pack
		in	mm	in	mm			
WD20-150	Black	1-½	43.1	1.70	43.1	200	0.24	200' - Coil
WD20-200	Black	2	55.8	2.20	55.8	200	0.31	200' - Coil
WD20-250	Black	2-½	68.5	2.70	68.5	200	0.45	200' - Coil
WD20-300	Black	3	81.3	3.20	81.3	200	0.46	200' - Coil
WD20-400	Black	4	108.0	4.25	108.0	200	0.67	200' - Coil
WD20-600	Black	6	158.7	6.25	158.7	150	1.14	200' - Coil
WD20-800	Black	8	209.3	8.31	209.3	150	1.51	200' - Coil
WD20-1000	Black	10	263.0	10.35	263.0	150	2.25	50' - Coil
WD20OR-400	Orange	4	108.0	4.25	108.0	200	0.67	200' - Coil
WD20OR-600	Orange	6	158.7	6.25	158.7	150	1.14	200' - Coil
WD20OR-800	Orange	8	209.3	8.31	209.3	150	1.51	200' - Coil



Camlock C x E



Type B

Part Number	Hose Size	Fitting A	Fitting B	Length	Attaching Method
				ft	
WD20-150PF50	1-½	FNPSH	MNPSH	50	Expanded
WD20-150CE50	1-½	C	E	50	Crimp
WD20-200CE50	2	C	E	50	Crimp
WD20-300CE50	3	C	E	50	Crimp
WD20-400CE50	4	C	E	50	Crimp
WD20-600CE50	6	C	E	50	Crimp
WD20-400BS50	4	Ball - Type B	Socket - Type B	50	Crimp
WD20-600BS50	6	Ball - Type B	Socket - Type B	50	Crimp
WD20-800BS50	8	Ball - Type B	Socket - Type B	50	Crimp

Other lengths and fitting combinations are available.

BECAUSE WE CONTINUALLY EXAMINE WAYS TO IMPROVE OUR PRODUCTS, WE RESERVE THE RIGHT TO ALTER SPECIFICATIONS WITHOUT NOTICE.



## WD95 TPU WATER DISCHARGE HOSE



**Tube:** One-piece through the weave TPU  
**Reinforcement:** Circular woven synthetic yarns  
**Cover:** Black abrasion resistant TPU (polyurethane)  
**Temperature:** -50°C to +70°C (-58°F to +160°F)  
**Application:** Designed for construction sites, waste water industry, agriculture and mining, transport of abrasive materials, flexible pipeline even in extreme terrain, irrigation and sludge disposal, for heavy duty service under toughest conditions. Perfectly prepared for hydraulic fraction in shale and oil fields.

Part Number	ID		OD		Max WP	Min BP	Weight	Length
	in	mm	in	mm	psi	psi	lbs/ft	
WD95-600-660-G	6				200	600	1.41	660' - Reel
WD95-800-660-G	8	8.30	210.8		200	600	2.35	660' - Reel
WD95-1000-660-G	10	10.33	262.4		200	600	2.75	660' - Reel
WD95-1200-660-G	12	12.33	313.2		150	450	3.40	660' - Reel

\* Includes aluminum Victaulic grooved couplings.

\* Also available with stainless Victaulic grooved couplings.



**FIELD ATTACHED CLAMP & GROOVED INSERT**

Part No.	Size
RGS-800	8"
RGS-1000	10"
RGS-1200	12"



**TWO BOLT GROOVED CLAMP**

Part No.	Size
GBC-800	8"
GBC-1000	10"
GBC-1200	12"



**PLATED STEEL GROOVED INSERT**

Part No.	Size
CNG-800	8"
CNG-1000	10"
CNG-1200	12"

\*Sold as sets only.

BECAUSE WE CONTINUALLY EXAMINE WAYS TO IMPROVE OUR PRODUCTS, WE RESERVE THE RIGHT TO ALTER SPECIFICATIONS WITHOUT NOTICE.

# Water Discharge Hose





## WD30 HEAVY DUTY CHILLER/WATER DISCHARGE HOSE - 150



**Tube:** Black synthetic rubber  
**Reinforcement:** Synthetic fiber  
**Cover:** Black synthetic rubber  
**Temperature:** -35°C to +80°C (-30°F to +180°F)  
**Application:** A heavy duty discharge hose used for rental/construction portable pumps and general water service.

**Branding:** FORSAFLEX WD30-400 4" HEAVY DUTY CHILLER/WATER DISCHARGE HOSE 150 PSI MAX WP

Water Discharge Hose

Part Number						Standard Pack
	ID	OD		Max WP	Weight	
	in	in	mm	psi	lbs/ft	
WD30-150	1-½	1.78	45.1	150	0.49	50/100' - Coil
WD30-200	2	2.32	58.8	150	0.66	50/100' - Coil
WD30-250	2-½	2.81	71.5	150	0.86	50/100' - Coil
WD30-300	3	3.38	86.2	150	1.35	50/100' - Coil
WD30-400	4	4.37	110.6	150	1.52	50/100' - Coil
WD30-500	5	5.40	138.0	150	2.25	50/100' - Coil
WD30-600	6	6.46	164.4	150	2.84	50/100' - Coil
WD30-800	8	8.54	217.0	150	4.20	50/100' - Coil
WD30-1000	10	10.55	268.0	150	5.78	50' - Coil

## WD30 HD RUBBER CHILLER/WATER DISCHARGE ASSEMBLIES



Part Number	Hose Size	Fitting A	Fitting B	Length	Attaching Method
				ft	
WD30-200CE50	2	Aluminum C	Aluminum E	50	Crimp
WD30-300CE50	3	Aluminum C	Aluminum E	50	Crimp
WD30-400CE50	4	Aluminum C	Aluminum E	50	Crimp
WD30-600CE50	6	Aluminum C	Aluminum E	50	Crimp
WD30-200CE50-BR	2	Brass C	Brass E	50	Crimp
WD30-300CE50-BR	3	Brass C	Brass E	50	Crimp
WD30-400CE50-BR	4	Brass C	Brass E	50	Crimp
WD30-400BS50	4	Ball - Type B	Socket - Type B	50	Crimp
WD30-600BS50	6	Ball - Type B	Socket - Type B	50	Crimp
WD30-800BS50	8	Ball - Type B	Socket - Type B	50	Crimp

Other lengths and fitting combinations are available.





BECAUSE WE CONTINUALLY EXAMINE WAYS TO IMPROVE OUR PRODUCTS, WE RESERVE THE RIGHT TO ALTER SPECIFICATIONS WITHOUT NOTICE.



## WD32 WATER JETTING 800

**Tube:** NBR/SBR, light oil resistance  
**Reinforcement:** Synthetic fiber  
**Cover:** Black synthetic rubber  
**Temperature:** -30°C to +85°C (-22°F to +185°F)  
**Application:** Stripping layers from hard surfaces, strip mining and washdown applications. Contact factory for proper fitting recommendation and coupling procedure.

**Branding:** FORSAFLEX WD32-400 4" WATER JETTING 800 PSI MAX WP

Part Number						Standard Pack
	ID	OD		Max WP	Weight	
	in	in	mm	psi	lbs/ft	
WD32-300	3	3.87	98.2	800	2.50	100' - Coil
WD32-400	4	5.02	127.6	800	3.70	100' - Coil
WD32-600	6	7.10	180.4	600	5.60	100' - Coil

BECAUSE WE CONTINUALLY EXAMINE WAYS TO IMPROVE OUR PRODUCTS, WE RESERVE THE RIGHT TO ALTER SPECIFICATIONS WITHOUT NOTICE.

# Water Discharge Hose




## WD35/WD38 SJ/DJ INDUSTRIAL MILL DISCHARGE






**Tube:** Black synthetic rubber  
**Cover:** Single/double jacket, synthetic fiber  
**Temperature:** -31°C to +85°C (-25°F to +185°F)  
**Application:** A very economical pump discharge and washdown hose.  
**Not approved for fire fighting service.**

Water Discharge Hose

### WD35 - Single Jacket

Part Number	 ID	Bowl Size	 Working	 Weight	Standard Pack
	in		psi	lbs/ft	
WD35-100	1	1-3/16	150	0.15	50/100' - Coil
WD35-150	1-1/2	1-3/4	150	0.23	50/100' - Coil
WD35-200	2	2-1/4	150	0.28	50/100' - Coil
WD35-250	2-1/2	2-3/4	150	0.39	50/100' - Coil
WD35-300	3	3-5/16	150	0.50	50/100' - Coil
WD35-400	4	4-3/8	150	0.66	50/100' - Coil

### WD38 - Double Jacket

Part Number	 ID	Bowl Size	 Working	 Weight	Standard Pack
	in		psi	lbs/ft	
WD38-100	1	1-3/8	250	0.19	50/100' - Coil
WD38-150	1-1/2	1-13/16	250	0.26	50/100' - Coil
WD38-200	2	2-5/16	250	0.33	50/100' - Coil
WD38-250	2-1/2	2-13/16	250	0.45	50/100' - Coil
WD38-300	3	3-3/8	250	0.61	50/100' - Coil
WD38-400	4	4-1/2	250	0.85	50/100' - Coil

## WD35 INDUSTRIAL MILL DISCHARGE ASSEMBLIES



NPSH F x M

Part Number	Hose Size	Fitting A	Fitting B	Length	Attaching Method
				ft	
WD35-150PF50	1-1/2	FNPSH	MNPSH	50	Expanded
WD35-250CSA50	2-1/2	FCSA	MCSA	50	Expanded
WD35-150FC50	1-1/2	Forestry	Forestry	50	Expanded
WD35-150FC100	1-1/2	Forestry	Forestry	100	Expanded

Other lengths and fitting combinations are available.




BECAUSE WE CONTINUALLY EXAMINE WAYS TO IMPROVE OUR PRODUCTS, WE RESERVE THE RIGHT TO ALTER SPECIFICATIONS WITHOUT NOTICE.



## WD45 AVALANCHE SNOWMAKING

**Tube:** Extremely smooth black synthetic rubber  
**Reinforcement:** Woven filament polyester  
**Cover:** Woven filament polyester  
**Temperature:** As low as -48°C (-55°F)  
**Application:** Designed for snowmaking, featuring a high performance construction.

**Branding:** FORSAFLEX WD45-200 2" AVALANCHE SNOWMAKING 800 PSI MAX WP

Part Number		Bowl Size			Standard Pack
	in		psi	lbs/ft	
WD45-150	1-½	1-15/16	800	0.24	100' - Coil
WD45-200	2	2-5/16	800	0.32	100' - Coil
WD45-250	2-½	2-13/16	800	0.44	100' - Coil

Part Number	Hose Size	Fitting A	Fitting B	Length	Attaching Method
				ft	
WD45-150CE15	1-½"	1-½" - C	1-½" - E	15	Internal Expanded
WD45-150CE25	1-½"	1-½" - C	1-½" - E	25	Internal Expanded
WD45-150CE50	1-½"	1-½" - C	1-½" - E	50	Internal Expanded
WD45-150CE100	1-½"	1-½" - C	1-½" - E	100	Internal Expanded
WD45-150CE15-2	1-½"	2" - C	2" - E	15	Internal Expanded
WD45-150CE25-2	1-½"	2" - C	2" - E	25	Internal Expanded
WD45-150CE50-2	1-½"	2" - C	2" - E	50	Internal Expanded
WD45-150CE100-2	1-½"	2" - C	2" - E	100	Internal Expanded
WD45-200CE15	2"	2" - C	2" - E	15	Internal Expanded
WD45-200CE25	2"	2" - C	2" - E	25	Internal Expanded
WD45-200CE50	2"	2" - C	2" - E	50	Internal Expanded
WD45-200CE100	2"	2" - C	2" - E	100	Internal Expanded
WD45-250CE15	2-½"	2-½" - C	2-½" - E	15	Internal Expanded
WD45-250CE25	2-½"	2-½" - C	2-½" - E	25	Internal Expanded
WD45-250CE50	2-½"	2-½" - C	2-½" - E	50	Internal Expanded
WD45-250CE100	2-½"	2-½" - C	2-½" - E	100	Internal Expanded

BECAUSE WE CONTINUALLY EXAMINE WAYS TO IMPROVE OUR PRODUCTS, WE RESERVE THE RIGHT TO ALTER SPECIFICATIONS WITHOUT NOTICE.

# Water Discharge Hose



## WD70 WHITE HOT WATER WASHDOWN HOSE

- Tube:** EPDM
- Reinforcement:** Synthetic fiber
- Cover:** EPDM with Microban
- Temperature:** -40°C to +99°C (-40°F to +210°F)
- Application:** A high-quality hose for hot water cleanup service in food processing plants, dairies, packing houses, bottling plants, breweries, canneries, and creameries.

Part Number	ID		OD		Max WP	Weight	Standard Pack
	in	mm	in	mm	psi	lbs/ft	
WD70-050	1/2	12.7	0.91	23.1	300	0.27	500' - Reel
WD70-075	3/4	19.0	1.18	29.9	300	0.40	500' - Reel
WD70-100	1"	25.4	1.50	38.1	300	0.60	450' - Reel

## WD90 GREEN PAPERMILL WASHDOWN



- Tube:** Black synthetic rubber
- Reinforcement:** Synthetic fiber
- Cover:** Green abrasion resistant synthetic rubber
- Temperature:** -35°C to +80°C (-31°F to +176°F)
- Application:** Suitable for hot or cold water washdown service in paper mills. Hose incorporates an integral built-in tapered rubber nozzle.

**Branding:** FORSAFLEX WD90-100 1" PAPERMILL WASHDOWN HOSE 250 PSI MAX WP

Part Number	ID		OD		Max WP	Weight	Standard Pack
	in	mm	in	mm	psi @ 20°C / 70°F	lbs/ft	
WD90-075	3/4	19.0	1.26	32.0	250	0.40	50' - Coil
WD90-100	1"	25.4	1.50	37.0	250	0.56	50' - Coil

\* Both the 3/4" and 1" built-in tapered nozzle have a 3/8" ID orifice

BECAUSE WE CONTINUALLY EXAMINE WAYS TO IMPROVE OUR PRODUCTS, WE RESERVE THE RIGHT TO ALTER SPECIFICATIONS WITHOUT NOTICE.