

Water Suction Hose

HOSE

15

Water Suction Hose



WS50 HD RUBBER WATER SUCTION & DISCHARGE

- Tube:** Black synthetic rubber
- Reinforcement:** A high tensile steel helix embedded between layers of textile cords
- Cover:** Black synthetic rubber
- Temperature:** -30°C to +85°C (-25°F to +185°F)
- Application:** A heavy duty wire reinforced rubber suction hose for rental, construction, quarries and general industrial use.

Branding: FORSAFLEX WS50-200 2" HD WATER SUCTION HOSE 150 PSI MAX WP

Part Number	ID		OD		Max WP	Min BR	Vacuum Inches	Weight	Standard Pack
	in	mm	in	mm	psi	in	Hg	lbs/ft	
WS50-150	1-½	49.0	1.93	49.0	150	6.5	29	0.80	100' - Coil
WS50-200	2	62.8	2.47	62.8	150	8.0	29	1.10	100' - Coil
WS50-250	2-½	75.5	2.97	75.5	150	10.0	29	1.75	100' - Coil
WS50-300	3	89.2	3.51	89.2	150	12.0	29	2.24	100' - Coil
WS50-400	4	115.6	4.55	115.6	150	18.0	29	2.79	100' - Coil
WS50-500	5	144.0	5.68	144.0	150	26.0	29	3.25	100' - Coil
WS50-600	6	166.4	6.55	166.4	150	31.0	29	5.75	20/100' - Coil
WS50-800	8	223.2	8.79	223.2	150	42.0	29	6.59	20/100' - Coil
WS50-1000	10	276.0	10.86	276.0	150	50.0	29	10.25	20' - LG
WS50-1200	12	327.0	12.87	327.0	150	60.0	29	13.50	20' - LG

BECAUSE WE CONTINUALLY EXAMINE WAYS TO IMPROVE OUR PRODUCTS, WE RESERVE THE RIGHT TO ALTER SPECIFICATIONS WITHOUT NOTICE.

Water Suction Hose

WS50 RUBBER SUCTION & DISCHARGE ASSEMBLIES



Camlock C x E

Part Number	Hose Size	Fitting A	Fitting B	Length	Attaching Method
				ft	
WS50-150CE20	1-½	C	E	20	Crimp
WS50-200CE20	2	C	E	20	Crimp
WS50-300CE20	3	C	E	20	Crimp
WS50-400CE20	4	C	E	20	Crimp
WS50-600CE20	6	C	E	20	Crimp
WS50-800CE20	8	C	E	20	Crimp

Other lengths available.



C x NPT

Part Number	Hose Size	Fitting A	Fitting B	Length	Attaching Method
				ft	
WS50-150CM20	1-½	C	NPT	20	Crimp
WS50-200CM20	2	C	NPT	20	Crimp
WS50-300CM20	3	C	NPT	20	Crimp
WS50-400CM20	4	C	NPT	20	Crimp
WS50-600CM20	6	C	NPT	20	Crimp

Other lengths available.



Type B



Type A

Part Number	Hose Size	Fitting A	Fitting B	Length	Attaching Method
				ft	
WS50-400BS20	4	Ball - Type B	Socket - Type B	20	Crimp
WS50-600BS20	6	Ball - Type B	Socket - Type B	20	Crimp
WS50-800BS20	8	Ball - Type B	Socket - Type B	20	Crimp
WS50-1000BS20	10	Ball - Type B	Socket - Type B	20	Crimp
WS50-1200BS20	12	Ball - Type B	Socket - Type B	20	Crimp
WS50-1000BS20-A	10	Ball - Type A	Socket - Type A	20	Crimp
WS50-1200BS20-A	12	Ball - Type A	Socket - Type A	20	Crimp

Other lengths available.



Fixed x Floating

Part Number	Hose Size	Fitting A	Fitting B	Length	Attaching Method
				ft	
WS50-400FFL20	4	Fixed Flange	Floating Flange	20	Crimp
WS50-600FFL20	6	Fixed Flange	Floating Flange	20	Crimp
WS50-800FFL20	8	Fixed Flange	Floating Flange	20	Crimp
WS50-1000FFL20	10	Fixed Flange	Floating Flange	20	Crimp

Other lengths available.

BECAUSE WE CONTINUALLY EXAMINE WAYS TO IMPROVE OUR PRODUCTS, WE RESERVE THE RIGHT TO ALTER SPECIFICATIONS WITHOUT NOTICE.

Water Suction Hose

HOSE

15

Water Suction Hose



WS52 PREMIUM EPDM SUCTION HOSE

- Tube:** Black EPDM
Reinforcement: A high tensile steel helix embedded between layers of textile cords
Cover: Black weather and abrasion resistant EPDM rubber
Temperature: -30°C to +95°C (-22°F to +203°F)
Application: EPDM suction hose is designed for improved weathering and chemical resistance. A heavy duty wire reinforced rubber suction hose for rental, construction, quarries and general industrial use. It is often used for glycol supply lines on portable heating units.

Branding: FORSAFLEX WS52-200 2" EPDM SUCTION HOSE 150 PSI MAX WP

Part Number	ID		OD		Max WP	Min BR	Vacuum Inches	Weight	Standard Pack
	in	mm	in	mm	psi	in	Hg	lbs/ft	
WS52-075	3/4	19.0	1.18	30.0	200	4.0	29	0.45	100' - Coil
WS52-100	1	25.4	1.43	36.4	200	5.4	29	0.54	100' - Coil
WS52-125	1-1/4	31.8	1.65	41.9	200	6.3	29	0.66	100' - Coil
WS52-150	1-1/2	38.1	1.89	48.0	200	7.0	29	0.70	100' - Coil
WS52-200	2	50.8	2.47	62.8	150	10.0	29	1.05	100' - Coil
WS52-300	3	76.2	3.47	88.2	150	12.0	29	1.50	100' - Coil
WS52-400	4	101.6	4.55	115.6	150	19.0	29	2.65	100' - Coil

WS55 CORRUGATED EPDM SUCTION HOSE

- Tube:** Black EPDM
Reinforcement: A high tensile steel helix embedded between layers of textile cords
Cover: Black weather and abrasion resistant EPDM rubber
Temperature: -30°C to +95°C (-22°F to +203°F)
Application: EPDM suction hose is designed for improved weathering and chemical resistance. A heavy duty wire reinforced rubber suction hose for rental, construction, quarries and general industrial use.

Branding: FORSAFLEX WS55-600 6" EPDM SUCTION HOSE 150 PSI MAX WP



Part Number	ID		OD		Max WP	Min BR	Vacuum Inches	Weight	Standard Pack
	in	mm	in	mm	psi	in	Hg	lbs/ft	
WS55-600	6	152.4	6.69	170.0	150	20.0	29	5.10	100'/20' - Coil
WS55-800	8	203.2	8.82	224.0	150	32.0	29	8.20	100'/20' - Coil
WS55-1000	10	254.0	10.91	277.0	150	40.0	29	11.55	100'/20' - Coil
WS55-1200	12	304.8	13.50	342.9	150	60.0	29	16.60	100'/20' - Coil

BECAUSE WE CONTINUALLY EXAMINE WAYS TO IMPROVE OUR PRODUCTS, WE RESERVE THE RIGHT TO ALTER SPECIFICATIONS WITHOUT NOTICE.






Water Suction Hose



WS60 GREEN PVC SUCTION



Tube: Clear PVC
Reinforcement: PVC helix
Cover: Clear PVC
Temperature: -20°C to +70°C (-4°F to +158°F)
Application: For rental and construction pumps, septic tank, marine pump out service and hydro-seeding. PVC is resistant to some chemicals, acids and alkalis.

Part Number					Vacuum Inches			Standard Pack
	ID	OD		Max WP	Inches	Min BR	Weight	
	in	in	mm	psi @ 20°C / 70°F	Hg	in	lbs/ft	
WS60-075	3/4	1.01	25.6	110	28	3.0	0.19	100' - Coil
WS60-100	1	1.26	32.0	85	28	3.0	0.26	100' - Coil
WS60-125	1-1/4	1.56	39.6	85	28	4.0	0.35	100' - Coil
WS60-150	1-1/2	1.83	46.5	70	28	5.0	0.46	100' - Coil
WS60-200	2	2.32	59.0	65	28	7.0	0.66	100' - Coil
WS60-250	2-1/2	2.87	73.0	65	28	8.0	0.87	100' - Coil
WS60-300	3	3.43	87.0	60	28	10.0	1.24	100' - Coil
WS60-400	4	4.50	114.7	50	28	15.0	1.85	100' - Coil
WS60-500	5	5.58	149.3	45	28	22.0	2.42	100' - Coil
WS60-600	6	6.75	171.4	40	28	30.0	3.39	100' - Coil
WS60-800	8	9.18	225.0	30	28	35.0	5.97	20' - Coil

WS60 GREEN PVC SUCTION ASSEMBLIES



Camlock C x E



Camlock C x NPT

Part Number	Hose Size	Fitting A	Fitting B	Length	Attaching Method
				ft	
WS60-150CE20	1-1/2	C	E	20	Band Clamps
WS60-200CE20	2	C	E	20	Band Clamps
WS60-300CE20	3	C	E	20	Band Clamps
WS60-400CE20	4	C	E	20	Band Clamps
WS60-600CE20	6	C	E	20	Band Clamps
WS60-150CM20	1-1/2	C	NPT	20	Band Clamps
WS60-200CM20	2	C	NPT	20	Band Clamps
WS60-300CM20	3	C	NPT	20	Band Clamps
WS60-400CM20	4	C	NPT	20	Band Clamps
WS60-600CM20	6	C	NPT	20	Band Clamps

Other lengths are available.

BECAUSE WE CONTINUALLY EXAMINE WAYS TO IMPROVE OUR PRODUCTS, WE RESERVE THE RIGHT TO ALTER SPECIFICATIONS WITHOUT NOTICE.

Water Suction Hose

HOSE

15






Water Suction Hose



WS62 CLEAR/WHITE PVC SUCTION



Tube: Clear PVC
Reinforcement: PVC helix
Cover: Clear PVC
Temperature: -20°C to +70°C (-4°F to +158°F)
Application: For rental and construction pumps, septic tank, marine pump out service and hydro-seeding. PVC is resistant to some chemicals, acids and alkalis.

Part Number					Vacuum Inches			Standard Pack
	in	in	mm	psi @ 20°C / 70°F	Hg	in	lbs/ft	
WS62-075	3/4	1.01	25.6	110	28	3.0	0.19	100' - Coil
WS62-100	1	1.26	32.0	85	28	3.0	0.26	100' - Coil
WS62-125	1-1/4	1.56	39.6	85	28	4.0	0.35	100' - Coil
WS62-150	1-1/2	1.83	46.5	70	28	5.0	0.46	100' - Coil
WS62-200	2	2.32	59.0	65	28	7.0	0.66	100' - Coil
WS62-250	2-1/2	2.87	73.0	65	28	8.0	0.87	100' - Coil
WS62-300	3	3.43	87.0	60	28	10.0	1.24	100' - Coil
WS62-400	4	4.50	114.7	50	28	15.0	1.85	100' - Coil
WS62-500	5	5.58	149.3	45	28	22.0	2.42	100' - Coil
WS62-600	6	6.75	171.4	40	28	30.0	3.39	100' - Coil
WS62-800	8	9.18	225.0	30	28	35.0	5.97	20' - Coil

WS62 CLEAR PVC SUCTION ASSEMBLIES



Camlock C x E



Camlock C x NPT

Part Number	Hose Size	Fitting A	Fitting B	Length	Attaching Method
				ft	
WS62-150CE20	1-1/2	C	E	20	Band Clamp
WS62-200CE20	2	C	E	20	Band Clamp
WS62-300CE20	3	C	E	20	Band Clamp
WS62-400CE20	4	C	E	20	Band Clamp
WS62-150CM20	1-1/2	C	NPT	20	Band Clamp
WS62-200CM20	2	C	NPT	20	Band Clamp
WS62-300CM20	3	C	NPT	20	Band Clamp
WS62-400CM20	4	C	NPT	20	Band Clamp

BECAUSE WE CONTINUALLY EXAMINE WAYS TO IMPROVE OUR PRODUCTS, WE RESERVE THE RIGHT TO ALTER SPECIFICATIONS WITHOUT NOTICE.

Water Suction Hose



WS64 COLD TEMP PVC SUCTION



Tube: Clear low temp PVC
Reinforcement: Blue PVC helix
Cover: Clear low temp PVC
Temperature: -40°C to +65°C (-40°F to +150°F)
Application: A flexible hose for construction pumps, septic tank & marine pump-out service. Resistant to some chemicals, mild acids & alkalis. Specially formulated compounds allow for increased flexibility at low temperatures.

Part Number					Vacuum Inches			Standard Pack
	in	in	mm	psi @ 20°C / 70°F	Hg	in	lbs/ft	
WS64-075	3/4	1.01	25.6	115	29	3.0	0.19	100' - Coil
WS64-100	1	1.26	32.0	90	29	3.0	0.22	100' - Coil
WS64-125	1-1/4	1.56	39.6	90	29	4.0	0.36	100' - Coil
WS64-150	1-1/2	1.79	45.5	90	29	5.0	0.48	100' - Coil
WS64-200	2	2.35	59.8	90	29	7.0	0.62	100' - Coil
WS64-250	2-1/2	2.87	73.0	70	29	8.0	0.87	100' - Coil
WS64-300	3	3.43	87.0	65	29	10.0	1.23	100' - Coil
WS64-400	4	4.49	114.0	55	29	15.0	1.83	100' - Coil
WS64-500	5	5.57	141.5	45	28	25.0	2.42	100' - Coil
WS64-600	6	6.69	170.0	40	28	30.0	3.36	100' - Coil



Camlock C x E



Camlock C x NPT

WS64 COLD TEMP PVC ASSEMBLIES

Part Number	Hose Size	Fitting A	Fitting B	Length	Attaching Method
				ft	
WS64-150CE20	1-1/2	C	E	20	Band Clamp
WS64-200CE20	2	C	E	20	Band Clamp
WS64-300CE20	3	C	E	20	Band Clamp
WS64-400CE20	4	C	E	20	Band Clamp
WS64-150CM20	1-1/2	C	NPT	20	Band Clamp
WS64-200CM20	2	C	NPT	20	Band Clamp
WS64-300CM20	3	C	NPT	20	Band Clamp
WS64-400CM20	4	C	NPT	20	Band Clamp


BECAUSE WE CONTINUALLY EXAMINE WAYS TO IMPROVE OUR PRODUCTS, WE RESERVE THE RIGHT TO ALTER SPECIFICATIONS WITHOUT NOTICE.

Water Suction Hose

HOSE

15

Water Suction Hose



WS65 HD PVC SUCTION (SR STYLE)



Tube: Clear PVC
Reinforcement: Orange PVC helix with synthetic fiber
Cover: Clear PVC
Temperature: -20°C to +65°C (-4°F to +150°F)
Application: Good for both suction and discharge applications, this heavy duty hose can be used for rental/construction pumping as well as fish suction hose.

Part Number	ID		OD		Max WP	Min BR	Vacuum Inches	Weight	Standard Pack
	in	mm	in	mm	psi @ 20°C / 70°F	in	Hg	lbs/ft	
WS65-200	2	50.8	2.60	66.0	100	4.0	29.0	0.70	100' - Coil
WS65-300	3	76.2	3.62	92.0	100	6.3	28.0	1.13	100' - Coil
WS65-400	4	101.6	4.76	121.0	75	7.1	28.0	1.74	100' - Coil
WS65-600	6	152.4	7.17	182.1	70	10.2	28.0	3.88	20', 60', 100' - Coil
WS65-800	8	203.2	9.21	234.0	60	15.7	28.0	5.54	20' - 25' - Length
WS65-1000	10	254.0	11.63	295.4	40	25.0	28.0	8.90	20' - 25' - Length
WS65-1200	12	304.8	13.66	347.0	30	45.0	25.0	10.30	20' - Length

* Counter-Clockwise / Left Hand Helix

WS65 HD PVC SUCTION ASSEMBLIES (SR STYLE)



Camlock C x E

Part Number	Hose Size	Fitting A	Fitting B	Length	Attaching Method
				ft	
WS65-200CE20	2	C	E	20	Crimp
WS65-300CE20	3	C	E	20	Crimp
WS65-400CE20	4	C	E	20	Crimp
WS65-600CE20	6	C	E	20	Crimp



Type B

Part Number	Hose Size	Fitting A	Fitting B	Length	Attaching Method
				ft	
WS65-400BS20	4	Ball - Type B	Socket - Type B	20	Crimp
WS65-600BS20	6	Ball - Type B	Socket - Type B	20	Crimp
WS65-800BS20	8	Ball - Type B	Socket - Type B	20	Crimp
WS65-1000BS20	10	Ball - Type B	Socket - Type B	20	Crimp
WS65-1200BS20	12	Ball - Type B	Socket - Type B	20	Crimp
WS65-1000BS20-A	10	Ball - Type A	Socket - Type A	20	Crimp
WS65-1200BS20-A	12	Ball - Type A	Socket - Type A	20	Crimp



Type A

BECAUSE WE CONTINUALLY EXAMINE WAYS TO IMPROVE OUR PRODUCTS, WE RESERVE THE RIGHT TO ALTER SPECIFICATIONS WITHOUT NOTICE.

Water Suction Hose



WS62 PVC AIR SEEDER



Tube: PVC
Reinforcement: PVC helix
Cover: PVC
Temperature: -20°C to +70°C (-4°F to +158°F)
Application: Agricultural air seeder equipment.

Part Number	Helix/Cover	ID		OD		Max WP psi	Vacuum Inches Hg	Min BR in	Weight lbs/ft	Standard Pack
		in	mm	in	mm					
WS62-075	White/clear	3/4	19.0	1.00	25.4	86	28	3.0	0.19	100' Coil
WS62-100	White/clear	1	25.4	1.25	31.8	86	28	3.0	0.26	100' Coil
WS62-100BK	Black/clear	1	25.4	1.25	31.8	86	28	3.0	0.26	100' Coil
WS62-100SBK	Solid Black	1	25.4	1.25	31.8	86	28	3.0	0.26	100' Coil
WS62-125	White/clear	1-1/4	31.8	1.47	37.3	80	28	4.0	0.35	100' Coil
WS62-150	White/clear	1-1/2	38.1	1.77	45.0	70	28	5.0	0.46	100' Coil
WS62-200	White/clear	2	50.8	2.30	58.4	65	28	7.0	0.66	100' Coil
WS62-250	White/clear	2-1/2	63.5	2.84	72.1	65	28	8.0	0.87	100' Coil
WS62-250BK	Black/clear	2-1/2	63.5	2.84	72.1	65	28	8.0	0.87	100' Coil
WS62-250SBK	Solid Black	2-1/2	63.5	2.84	72.1	65	28	8.0	0.87	100' Coil
WS62-300	White/clear	3	76.2	3.35	85.1	55	28	10.0	1.24	100' Coil
WS62-300BK	Black/clear	3	76.2	3.35	85.1	55	28	10.0	1.24	100' Coil



KURD POLYURETHANE AIR SEEDER

Tube: Polyurethane
Reinforcement: PVC helix
Cover: Polyurethane
Temperature: -29°C to +65°C (-20°F to +150°F)
Application: Designed for dry applications to provide longer hose life and lower operating costs versus rubber or PVC hoses.

Part Number	Helix/Cover	ID		OD		Max WP psi	Vacuum Inches Hg	Min BR in	Weight lbs/ft	Standard Pack
		in	mm	in	mm					
KURD-250BK	Black/clear	2-1/2	63.5	3.14	79.7	4.5	28	4.0	0.90	100' Coil
KURD-250RD	Red/clear	2-1/2	63.5	3.14	79.7	4.5	28	4.0	0.90	100' Coil

BECAUSE WE CONTINUALLY EXAMINE WAYS TO IMPROVE OUR PRODUCTS, WE RESERVE THE RIGHT TO ALTER SPECIFICATIONS WITHOUT NOTICE.

Water Suction Hose

WS80 EDPM SUCTION (GREEN-GR, BLUE-BL, RED-RD, YELLOW-YW)



Tube:
Cover:
Temperature:
Application:

Black smooth EPDM
Green, blue or red polyethylene helix
-40°C to +71°C (-40°F to +160°F)
For rental and construction pumps, septic tank, agricultural and marine pump out service. EPDM is resistant to some chemicals, acids and alkalis.



Part Number	ID		OD		Max WP	Min BR	Vacuum Inches	Weight	Standard Pack
	in	mm	in	mm	psi @ 20°C / 70°F	in	Hg	lbs/ft	
WS80-100GR	1	35.5	1.40	35.5	65	2	Full	0.28	100' - Coil
WS80-125GR	1-¼	41.4	1.63	41.4	60	3	Full	0.33	100' - Coil
WS80-150GR	1-½	49.0	1.93	49.0	50	3	Full	0.44	100' - Coil
WS80-200GR	2	63.8	2.51	63.8	50	5	Full	0.67	100' - Coil
WS80-250GR	2-½	78.0	3.07	78.0	45	5.5	Full	0.95	100' - Coil
WS80-300GR	3	91.5	3.60	91.5	45	7	Full	1.14	100' - Coil
WS80-400GR	4	119.5	4.70	119.5	40	11.5	Full	1.84	100' - Coil
WS80-600GR	6	174	6.85	174	30	20	28	3.07	100' - Coil

WS80 EDPM SUCTION ASSEMBLIES



Camlock C x E

Part Number	Hose Size	Fitting A	Fitting B	Length	Attaching Method
				ft	
WS80-150CE20GR	1-½	C	E	20	Clamp
WS80-200CE20GR	2	C	E	20	Clamp
WS80-300CE20GR	3	C	E	20	Clamp
WS80-400CE20GR	4	C	E	20	Clamp
WS80-600CE20GR	6	C	E	20	Clamp

Other lengths and fitting combinations are available.
Some colors are non-stock and may require minimum runs.

WS80 EDPM SUCTION ASSEMBLIES



Camlock C x NPT

Part Number	Hose Size	Fitting A	Fitting B	Length	Attaching Method
				ft	
WS80-150CM20GR	1-½	C	NPT	20	Clamp
WS80-200CM20GR	2	C	NPT	20	Clamp
WS80-300CM20GR	3	C	NPT	20	Clamp
WS80-400CM20GR	4	C	NPT	20	Clamp
WS80-600CM20GR	6	C	NPT	20	Clamp

Other lengths and fitting combinations are available.
Some colors are non-stock and may require minimum runs.

BECAUSE WE CONTINUALLY EXAMINE WAYS TO IMPROVE OUR PRODUCTS, WE RESERVE THE RIGHT TO ALTER SPECIFICATIONS WITHOUT NOTICE.

Water Suction Hose

WS75 HONEY BEE SUCTION HOSE



Tube & Cover: Black and yellow polyethylene
Temperature: -40°C to +65°C (-40°F to +150°F)
Application: Honey Bee is specifically designed for use in septic handling, retail, construction, dewatering, environmental clean-up, and sewer inspection equipment where extreme use and durability is required.
DO NOT USE FOR DISCHARGE APPLICATIONS.

Part Number	ID		OD		Length ft	Max WP psi @ 20°C / 70°F	Vacuum Inches Hg	Weight lbs/ft
	in	mm	in	mm				
WS75-200-3	2	70.0	2.76	70.0	3	15	27	0.72
WS75-200-15	2	70.0	2.76	70.0	15	15	27	0.72
WS75-200-25	2	70.0	2.76	70.0	25	15	27	0.72
WS75-200-30	2	70.0	2.76	70.0	30	15	27	0.72
WS75-200-50	2	70.0	2.76	70.0	50	15	27	0.72
WS75-200-60	2	70.0	2.76	70.0	60	15	27	0.72
WS75-300-3	3	103.0	4.06	103.0	3	7	27	1.36
WS75-300-15	3	103.0	4.06	103.0	15	7	27	1.36
WS75-300-25	3	103.0	4.06	103.0	25	7	27	1.36
WS75-300-30	3	103.0	4.06	103.0	30	7	27	1.36
WS75-300-50	3	103.0	4.06	103.0	50	7	27	1.36
WS75-300-60	3	103.0	4.06	103.0	60	7	27	1.36

WS77 220RS STYLE RUBBER SUCTION HOSE



Tube: Black synthetic rubber
Cover: Smooth Synthetic black rubber
Reinforcement: White PVC helix
Temperature: -40°C to +60°C (-40°F to +140°F)
Application: Lightweight and kink resistant for rough construction applications. Suitable for full vacuum.

Part Number	ID		OD		Max WP psi @ 20°C / 70°F	Vacuum Inches Hg	Weight lbs/ft	Standard Pack
	in	mm	in	mm				
WS77-200	2	60.5	2.38	60.5	50	29	0.74	100' - Coil
WS77-300	3	86.6	3.41	86.6	43	29	1.21	100' - Coil
WS77-400	4	114.3	4.5	114.3	38	29	2.01	100' - Coil

BECAUSE WE CONTINUALLY EXAMINE WAYS TO IMPROVE OUR PRODUCTS, WE RESERVE THE RIGHT TO ALTER SPECIFICATIONS WITHOUT NOTICE.