

Eagle 700 Metal Hose

EAGLE 700 Hose Assembly with SS 316 Flanges - Hydro Formed

- Construction:** SS 316L Corrugated Flexible Hose with SS 304 Double Wire Braiding
- Couplings:** TIG Welded with 150# SS 316 Swivel flanges at both ends with SS 316 Sch.40 Stub end.
- Safety:** 4:1



Quality Certifications & Testing:

- Hydrostatic and pneumatically tested.
- ISO 14001:2004
- PED Certified

Part #	Part #	ID	Nom ID	Nom OD	Static Bend Radius	Dynamic Bend Radius	Max WP	Weight	
								10'	20'
10 ft. length	20 ft length	in	in	in	in	in	psi		
106-0160-0710	106-0160-0720	1	1	1.63	3	9	1137	31	53
106-0320-0710	106-0320-0720	2	1.98	2.77	5	15	867	44	76
106-0480-0710	106-0480-0720	3	3.15	3.99	9	22	526	61	103
106-0640-0710	106-0640-0720	4	4.36	5.06	10	24	455	98	163
106-0960-0710	106-0960-0720	6	5.93	7.12	18	31	312	163	277
106-1280-0710	106-1280-0720	8	7.76	9.29	19	37	270	251	421
106-1600-0710	106-1600-0720	10	9.86	11.45	25	51	174	267	423
106-1920-0710	106-1920-0720	12	11.82	13.5	31	61	151	353	553



Liverpool Location ISO 9001:2015 Certified QMS by Intertek

Click for directions:

New England Region
Liverpool, NY 13088
(315) 451-2770

Great Lakes Region
Cheektowaga, NY 14225
(716) 684-8224

Mid-Atlantic Region
Charlotte, NC 28273
(704) 588-9920

Midwest Region
St. Louis, MO 63111
(314) 256-0833

Gulf Coast Region
Pasadena, TX 77503
(281) 930-7777

Download the JGB® Mobile App



Connect with us:



www.jgbhose.com