

Eagle Air®



HOSE ON REELS



BRANDING



REEL LABELS



FINAL PACKAGING

General Purpose EPDM Air & Water - 300 PSI - Red

Application: An economical multi-purpose air and water hose suitable for a wide range of industrial, construction and agricultural applications.

Tube: EPDM, black, antistatic, smooth

Reinforcement: 2 textile spiral (4 spiral in 1-1/2")

Cover: EPDM, red, resistant to heat, sunlight, ozone and weather

Branding: #” Eagle Air® EPDM 300 PSI WP

Temperature: -40°F / +212°F


Packaging: Reel-Core Plastic Reels

Lengths: mix. 90% of the reels in 1 piece, max 10% in up to 3 pieces; increments of 50ft

Safety Factor: 4:1

Part #	ID	OD	Max WP	Reinforcements	Min.Bend Radius	Length	Weight
	in	in	psi		in.	ft.	lbs/ft
001-0041-0300I	1/4	0.5	300	2	1.5	500	0.13
001-0051-0300I	5/16	0.6	300	2	1.9	500	0.18
001-0061-0300I	3/8	0.7	300	2	2.25	500	0.23
001-0081-0300I	1/2	0.8	300	2	3	500	0.32
001-0101-0300I	5/8	0.9	300	2	3.75	500	0.39
001-0121-0300I	3/4	1.1	300	2	4.5	500	0.50
001-0161-0300I	1	1.4	300	2	6	450	0.73
001-0201-0300I	1 1/4	1.7	300	2	7.5	400	1.04
001-0241-0300I	1 1/2	2.0	300	4	9	300	1.23

Note: If in any doubt regarding use, please contact JGB. The temperature of the medium must be lower than its boiling point.



Liverpool Location ISO 9001:2015 Certified QMS by Intertek

Download the JGB® Mobile App



Click for directions:

New England Region
Liverpool, NY 13088
(315) 451-2770

Great Lakes Region
Cheektowaga, NY 14225
(716) 684-8224

Mid-Atlantic Region
Charlotte, NC 28273
(704) 588-9920

Midwest Region
St. Louis, MO 63111
(314) 256-0833

Gulf Coast Region
Pasadena, TX 77503
(281) 930-7777

Connect with us:



www.jgbhose.com