

Eagle Composite UNI-VAPOR

Petroleum

Vapor Recovery Service Hose



Application: Petrochemical and petroleum Vapor recovery systems

Carcass: Multiple layers of polypropylene fabric, film and polyester barrier layers

Cover: Abrasion Resistant PVC impregnated fabric

Reinforcement: High tensile strength galvanized internal and external wire.

Temperature: -22°F to +176°F (-30°C to +80°C)

Branding: EAGLE COMPOSITE UNI-VAPOR 150 PSI

Safety Factor: 4:1

Couplings: Carbon or Stainless (304 or 316), MNPT or Flange, Camlock

Features:

- Complete product compatibility for safe handling of all types of oil based 100% aromatic and Vapor.
- Tough PVC outer cover resists to dragging, wear, abrasion, UV and ozone resistance having maximum durability and safety.
- Electrical continuity is achieved by the two wire bonded of the end fittings, this helps dissipate accumulated charge and to avoid static flash.
- Suitable for 0.9 Bar Vacuum

Part #	ID	Bend Radius	Max WP	Burst Pressure	Max Length	Weight
	in	in	PSI	PSI	ft	lbs/ft
009-0163-1000I	1	4.9	150	600	60	0.77
009-0243-1000I	1.5	5.9	150	600	60	0.94
009-0323-1000I	2	7.9	150	600	60	1.14
009-0483-1000I	3	11.0	150	600	60	1.80
009-0643-1000I	4	15.75	150	600	60	2.70
009-0963-1000I	6	22.50	150	600	60	6.10
009-1283-1000I	8	31.50	150	600	60	9.40



Liverpool Location ISO 9001:2015 Certified QMS by Intertek

Download the JGB® Mobile App



Click for directions:

New England Region
Liverpool, NY 13088
(315) 451-2770

Great Lakes Region
Cheektowaga, NY 14225
(716) 684-8224

Mid-Atlantic Region
Charlotte, NC 28273
(704) 588-9920

Midwest Region
St. Louis, MO 63111
(314) 256-0833

Gulf Coast Region
Pasadena, TX 77503
(281) 930-7777

Connect with us:



www.jgbhose.com