

Eagle Gravity Fuel Drop

Fuel Delivery Hose



Application: Designed to deliver gasoline, diesel fuel, kerosene and fuels with aromatic content to 40%.

Tube: NBR/PVC tube, smooth bore with embedded Safety Ohm ground wire in the hose wall

Reinforcement: Rigid clockwise PVC helix, one braid of high tensile polyester yarn reinforcement

Temperature: -10°F to +140°F

Lengths: 100 ft lengths

Features:

- ** Up to 50% lighter than conventional rubber hose.
- Higher transfer pressures.
- Easy to drag with "Go-Glide" external clockwise PVC helix.
- Safety Ohm ground wire embedded into hose wall to help prevent the build-up of static electricity. Wire must be secured to ground to dissipate static electricity.

Part #	ID	OD	Reinf. Spirals	MAX WP @ 68°F	Vacuum @ 68°F	Weight lb/ft	Min Bend Radius
	in	in		psi	mm/Hg		in
009-0324-0120I	2	2.68	1	70	29.9	1.13	5
009-0484-0120I	3	3.68	1	65	29.9	1.37	6
009-0644-0121I	4	4.8	1	65	29.9	2.16	8



Liverpool Location ISO 9001:2015 Certified QMS by Intertek

Download the JGB® Mobile App



Click for directions:

New England Region
Liverpool, NY 13088
(315) 451-2770

Great Lakes Region
Cheektowaga, NY 14225
(716) 684-8224

Mid-Atlantic Region
Charlotte, NC 28273
(704) 588-9920

Midwest Region
St. Louis, MO 63111
(314) 256-0833

Gulf Coast Region
Pasadena, TX 77503
(281) 930-7777

Connect with us:



www.jgbhose.com