

Eagle Gunitite 150 PSI Hose

Gunitite Application Hose

Application: Ultra wear resistant and thick tube, designed for high kink resistance and perfect flow, suitable for air pumping dry sand or cement mixtures to the water mixing nozzle in gunitite applications.

Tube: ¼" Pure Gum Rubber Tan

Reinforcement: Multiple plies of synthetic fabric with an imbedded static wire

Cover: Non marking Pure Gum Blend

Temperature: -22° to 185°F

Branding: Eagle Gunitite 150 PSI WP



Part #	ID	OD	WP	Burst Pressure	Weight	Std. Length
	in	in	psi	psi	lbs/ft	ft
014-0242-0150	1-1/2	2.38	150	450	1.17	100
014-0328-0150	2	2.88	150	450	1.46	100



Liverpool Location ISO 9001:2015 Certified QMS by Intertek

Download the JGB® Mobile App



Click for directions:

New England Region
Liverpool, NY 13088
(315) 451-2770

Great Lakes Region
Cheektowaga, NY 14225
(716) 684-8224

Mid-Atlantic Region
Charlotte, NC 28273
(704) 588-9920

Midwest Region
St. Louis, MO 63111
(314) 256-0833

Gulf Coast Region
Pasadena, TX 77503
(281) 930-7777

Connect with us:



www.jgbhose.com