

Eagle Heavy Duty Nitrile

NBR Lay Flat Frac Water Hose

Large Diameter Hose (LDH)



Application: Water discharge/transfer, drainage, irrigation installations, pumping of sludge and liquid fertilizers, chemical industry, refineries

Tube & Cover: Nitrile/PVC Blend, ribbed cover for maximum abrasion resistance

Reinforcement: 100% virgin high tenacity polyester jacket

Temperature: -22°F to 176°F

Color: Black

Package: Rolled, packed in carton or loaded on pallet

Standard Length: 660'

Mfg. Technology: Through-the-weave-technology without delamination issues
(See Oroflex 20 PVC/Nitrile Rubber Discharge Hose)

ID	WP	Burst	Wall Thickness	Tensile Strength	Weight
in	psi/bar	psi/bar	in	lbs	lbs/ft
6	290/20	725/50	0.16	51.600	1.7
8	200/13	566/39	0.17	89.066	2.6
10	200/13	566/39	0.17	100.310	3.0
12	150/10	450/31	0.17	134.481	4.0



Liverpool Location ISO 9001:2015 Certified QMS by Intertek

Click for directions:

New England Region
Liverpool, NY 13088
(315) 451-2770

Great Lakes Region
Cheektowaga, NY 14225
(716) 684-8224

Mid-Atlantic Region
Charlotte, NC 28273
(704) 588-9920

Midwest Region
St. Louis, MO 63111
(314) 256-0833

Gulf Coast Region
Pasadena, TX 77503
(281) 930-7777

Download the JGB® Mobile App



Connect with us:



www.jgbhose.com