

Eagle Honey Bee Hose

Wastewater

Polyethylene Liquid Suction & Wastewater Hose



Application: Pumps, rental and construction dewatering, trash pumps, septic & wastewater handling, standard-duty water suction

Tube: Flexible polyethylene (LDPE) tube

Reinforcement: Polyethylene (LDPE) ribs and cuffed ends

Temperature: -40°F to 150°F (Actual service temperature range is application dependent.)

Lengths: 2": 3/10/20/25/30/40/50/60 ft.

3": 3/20/25/30/50/60 ft.

Features:

Superior Flexibility! Corrugated tube and ribs provides high flexibility, perfect for maneuvering in tight areas such as portable toilets.

"Cold-Flex" Materials Hose remains flexible in sub-zero temperatures.

Crush Resistant Will spring back to original shape after being crushed, will not kink!

Easy Slide Helix Exposed ribs protect hose tube from cover wear, and allow hose to slide easily over rough surfaces. Easy-to-handle.

Leak Proof Cuffs Overmolded cuffs eliminate leaking and will not separate from the hose. Each cuff and unit is 100% factory tested.

Part #	ID	OD	WP	Vacuum Rating	Min Bend Radius	Weight
	in	in	psi @ 68°F	in. Hg @ 68°F	in	lbs/ft
004-0329-01001	2	2.76	15	29	3.5	0.65
004-0489-01001	3	4.06	7	29	6.5	1.2

NOTE: Service life may vary depending on operating conditions and type of material being conveyed.



Liverpool Location ISO 9001:2015 Certified QMS by Intertek

Download the JGB® Mobile App



Click for directions:

New England Region
Liverpool, NY 13088
(315) 451-2770

Great Lakes Region
Cheektowaga, NY 14225
(716) 684-8224

Mid-Atlantic Region
Charlotte, NC 28273
(704) 588-9920

Midwest Region
St. Louis, MO 63111
(314) 256-0833

Gulf Coast Region
Pasadena, TX 77503
(281) 930-7777

Connect with us:



www.jgbhose.com