

# EAGLE OILVAC

## 150 PSI Corrugated Vacuum Tank Service

**Application:** Designed for handling crude oil, frack solutions and slurries in oilfield vacuum tank service

**Note:** For applications up to 35% aromatics. Not for use with refined petroleum products or high concentrations of chemicals.

**Tube:** NBR/SBR – black, smooth, oil resistant

**Reinforcement:** High tensile textile cord; dual steel helix

**Cover:** NBR/SBR – black, flat corrugated with cloth impression, oil, abrasion, weather & ozone resistant

**Temperature:** -40°F to +185°F

**Branding:** EAGLE OILVAC 150 PSI WP

**Couplings:** Contact JGB for proper fitting recommendation and coupling procedure



Part #	ID	OD	Min Bend Radius	WP	Weight
	in	in	in	psi	lbs/ft
009-0322-0155I	2	2.48	5	150	1.09
009-0482-0155I	3	3.46	7.5	150	1.71
009-0642-0155I	4	4.53	12	150	2.29
009-0962-0155I	6	6.65	21	150	4.91
009-1282-0152I	8	8.86	31.5	150	8.62

\* Full Vacuum



Liverpool Location ISO 9001:2015 Certified QMS by Intertek

Download the JGB® Mobile App



Click for directions:

**New England Region**  
Liverpool, NY 13088  
(315) 451-2770

**Great Lakes Region**  
Cheektowaga, NY 14225  
(716) 684-8224

**Mid-Atlantic Region**  
Charlotte, NC 28273  
(704) 588-9920

**Midwest Region**  
St. Louis, MO 63111  
(314) 256-0833

**Gulf Coast Region**  
Pasadena, TX 77503  
(281) 930-7777

Connect with us:



[www.jgbhose.com](http://www.jgbhose.com)