

# Eagle Flo® Grey

## PVC Discharge Hose Light/ Medium Duty



**Application:** For light/medium duty water discharge service in agricultural, quarry, irrigation, mining, construction and industrial applications.

**Tube:** Black Pliovic™ compound

**Reinforcement:** 2-ply synthetic fabric

**Cover:** Grey Pliovic™ compound

**Temperature:** -10°F to 150°F

**Packaging:** 300' continuous one piece, coiled and banded

**Couplings:** Standard short shank aluminum, malleable or brass couplings

Part #	ID	OD	WP	Weight
	in	in	psi	lb/ft
008-0247-0075	1-1/2	1.72	90	0.19
008-0327-0080I	2	2.22	80	0.24
*	2-1/2	2.79	60	0.36
008-0487-0050I	3	3.31	50	0.40
008-0647-0110I	4	4.33	45	0.68
008-0967-0035	6	6.38	35	1.07

Note: Working pressures are rated at 72°F.

\* Non-stock, call JGB for availability.



Liverpool Location ISO 9001:2015 Certified QMS by Intertek

Click for directions:

**New England Region**  
Liverpool, NY 13088  
(315) 451-2770

**Great Lakes Region**  
Cheektowaga, NY 14225  
(716) 684-8224

**Mid-Atlantic Region**  
Charlotte, NC 28273  
(704) 588-9920

**Midwest Region**  
St. Louis, MO 63111  
(314) 256-0833

**Gulf Coast Region**  
Pasadena, TX 77503  
(281) 930-7777

Download the JGB® Mobile App



Connect with us:



www.jgbhose.com