

Mining

Eagle Mine[®] Spray



JGB Eagle Mine[®] Spray Hose

Application: Heavy-duty service requirements of underground mine spray applications, excellent choice for high pressure air applications in mining, construction and quarries.

Tube: Blend of synthetic elastomers, smooth, oil resistant, black

Reinforcement: Single high tensile steel braid

Cover: Yellow, blend of synthetic elastomers compound, smooth with cloth impression

Temperature: Suitable range -22°F to 212°F

Branding: EAGLE MINE[®] SPRAY 1000 PSI MSHA

Standard/Notice: MSHA approved cover

Features:

- Robust
- MSHA approved flame, oil and abrasion resistant cover
- Weather and ozone resistant

Part #	ID	OD	Wall	WP	Burst	Bend Radius	Weight	Length
	in	in	in	psi	psi	in	lbs/ft	ft
003-0123-1000I	3/4	1.10	0.15	1000	4000	9	0.41	100
003-0163-1001I	1	1.34	0.17	1000	4000	12	0.55	50
003-0163-1000I	1	1.34	0.17	1000	4000	12	0.55	100
003-0203-1000I	1-1/4	1.63	0.19	1000	4000	15	0.74	50
003-0203-1001I	1-1/4	1.63	0.19	1000	4000	15	0.74	100
003-0243-1001I	1-1/2	1.89	0.20	1000	4000	18	0.95	50
003-0243-1000I	1-1/2	1.89	0.20	1000	4000	18	0.95	100
003-0323-1000I	2	2.4	0.21	1000	4000	24	1.47	100



Liverpool Location ISO 9001:2015 Certified QMS by Intertek

Download the JGB[®] Mobile App



Click for directions:

New England Region
Liverpool, NY 13088
(315) 451-2770

Great Lakes Region
Cheektowaga, NY 14225
(716) 684-8224

Mid-Atlantic Region
Charlotte, NC 28273
(704) 588-9920

Midwest Region
St. Louis, MO 63111
(314) 256-0833

Gulf Coast Region
Pasadena, TX 77503
(281) 930-7777

Connect with us:



www.jgbhose.com