

Eagle Air®

Eagle Shop Air Hose

- Application:** Air compressor hose
- Tube:** SBR + NR
- Reinforcement:** 2 Spiral Polyester Yarns
- Cover:** EPDM
- Temperature:** -22°F to +176°F
- Branding:** 3/8" EAGLE AIR 300PSI MAX WP #Q##
- Oil Resistance:** Limited
- Packaging:** 50 ft. length each with shrink film
- Couplings:** 1/4 NPT x 18 Fitting at both ends
- Color:** Red



Part #	ID	OD	Standard Length	WP	Burst Pressure
	in	mm	ft	psi	psi
001-0061-0050I	3/8	16.5	50	300	900

Eagle Air Hybrid Hose

- Application:** Air compressor hose
- Tube:** Black PVC
- Reinforcement:** 2 Spiral Polyester Yarns
- Cover:** PVC "Eagle Hybrid"
- Temperature:** -13°F to +140°F
- Branding:** 3/8" EAGLE AIR HYBRID 300PSI MAX WP #Q##
- Oil Resistance:** Limited
- Packaging:** 50 ft. length each with shrink film
- Couplings:** 1/4 NPT x 18 Fitting at both ends
- Color:** Blue
- Unit Weight:** 7.3 Lbs. (20% lighter than the traditional rubber shop air)



Part #	ID	OD	Standard Length	WP	Burst Pressure
	in	mm	ft	psi	psi
001-0066-0050HI	3/8	9.5	50	300	900

Liverpool Location ISO 9001:2015 Certified QMS by Intertek



Download the JGB® Mobile App



Connect with us:



www.jgbhose.com

Click for directions:

New England Region
Liverpool, NY 13088
(315) 451-2770

Great Lakes Region
Cheektowaga, NY 14225
(716) 684-8224

Mid-Atlantic Region
Charlotte, NC 28273
(704) 588-9920

Midwest Region
St. Louis, MO 63111
(314) 256-0833

Gulf Coast Region
Pasadena, TX 77503
(281) 930-7777