

Eagle Water Discharge HD

Heavy-Duty Lay Flat Water Discharge Hose

Application: Use for agricultural, quarry, irrigation, mining, construction and industrial applications

Tube: Premium Red PVC

Reinforcement: Two spiral plies and longitudinal silk cords

Cover: Premium Red PVC

Temperature: -10°F To 150°F

Branding: EAGLE WATER DISCHARGE HD

Packaging: Cut and coupled to length

Couplings: Standard short shank aluminum, malleable or brass couplings, Steel Bauer



Part #	ID	Apprx. Wall Thickness	WP	Weight
	in	in	psi	lbs
008-0241-0150I	1.5	.075	150	.20
008-0321-0150I	2	.080	150	.28
008-0481-0150I	3	.095	150	.54
008-0641-0125I	4	.100	125	.67
008-0961-0115I	6	.105	115	1.25
008-1281-0070I	8	.110	70	1.48
008-1926-0040I	12	.112	40	2.43

Standard Size	MxF	CxE
1 1/2"x50'	A008-0241-1650	A008-0241-3550
2"x50'	A008-0321-1650	A008-0321-3550
3"x50'	A008-0481-1650	A008-0481-3550
4"x50'	A008-0641-1650	A008-0641-3550
6"x50'	A008-0961-1650	A008-0961-3550



Liverpool Location ISO 9001:2015 Certified QMS by Intertek

Click for directions:

New England Region
Liverpool, NY 13088
(315) 451-2770

Great Lakes Region
Cheektowaga, NY 14225
(716) 684-8224

Mid-Atlantic Region
Charlotte, NC 28273
(704) 588-9920

Midwest Region
St. Louis, MO 63111
(314) 256-0833

Gulf Coast Region
Pasadena, TX 77503
(281) 930-7777

Download the JGB® Mobile App



Connect with us:



www.jgbhose.com