

Chemical S&D Hose



Application: Chemical transfer hose designed for almost every common industrial chemical used in chemical transfer applications today. Not for steam service, can be open-end steam cleaned.

Tube: Ultra-High Molecular Weight polyethylene (UHMW-PE), clear, smooth, food quality, resistant to a wide range of chemicals

Reinforcement: High tensile textile cord, dual galvanized steel helix

Cover: EPDM - Green, smooth with cloth impression, resistant to weather, ozone and abrasion (Available in red, blue, yellow black and grey, white and orange - with 400 ft. order)

Temperature: -40°F to 212°F, 250°F (Intermittent)

Branding: EAGLECHEM® UHMWPE CHEMICAL TRANSFER 240 PSI MAX WP

Lengths: 100 ft.

Features:

- Lightweight
- Flexible
- Non-staining UHMW tube

Part #	ID in	OD in	MBR in	Vacuum in HG	WP psi	Weight lbs/ft
006-0129-0240I	3/4	1.19	3.5	29"	240	0.58
006-0166-0240I	1	1.47	4	29"	240	0.63
006-0246-0240I	1-1/2	2.08	4	29"	240	1.06
006-0326-0240I	2	2.58	6	29"	240	1.33
006-0406-0240I	2-1/2	3.03	10	29"	240	1.78
006-0480-0240I	3	3.61	16	29"	240	2.12
006-0646-0240I	4	4.61	24	29"	240	2.83
006-0960-0240I	6	6.89	36	26"	240	6.89



Liverpool Location ISO 9001:2015 Certified QMS by Intertek

Download the JGB® Mobile App



Click for directions:

New England Region
Liverpool, NY 13088
(315) 451-2770

Great Lakes Region
Cheektowaga, NY 14225
(716) 684-8224

Mid-Atlantic Region
Charlotte, NC 28273
(704) 588-9920

Midwest Region
St. Louis, MO 63111
(314) 256-0833

Gulf Coast Region
Pasadena, TX 77503
(281) 930-7777

Connect with us:



www.jgbhose.com