

Eagleflex II

Eagleflex II Pressure Washer Hose



Application: JGB Eagleflex II is specially designed for use on pressure washer machines with working pressures up to 6000 psi and temperatures up to 310°F.

Tube: Synthetic rubber, resistant against cold and hot water with usual cleaning agents

Reinforcement: Two braids of high tensile steel wire

Cover: Abrasion and ozone resistant synthetic rubber

Temperature: 14°F to 310°F

Branding: 3/8" EAGLEFLEX II PRESSURE WASHER HOSE 6000 PSI/310 DEG F #Q##

Packaging: 450 ft, 2 piece reels or cut-to-length coils

Couplings: Hydraulic 100R1 type, crimped to manufacturer specifications

Colors: Blue, Gray, Black

Features:

- Available in bulk, 50 ft., 100 ft., and custom lengths
- Lightweight and easy to handle
- A unique cover compound gives JGB Eagleflex II hoses the durability and flexibility to handle abrasion and normal cleaning chemicals used in the wash industry.

Part #			Nom ID	Thickness	OD	WP	Burst	Bend Radius	Weight
Black	Blue	Grey	in	in	in	psi	psi	in	lbs/ft
172-1006-4002I	172-1006-5801I	172-0067-5400I	3/8	0.4	0.64	6091	18,275	2.6	.255



Liverpool Location ISO 9001:2015 Certified QMS by Intertek

Download the JGB® Mobile App



Connect with us:



www.jgbhose.com

Click for directions:

New England Region
Liverpool, NY 13088
(315) 451-2770

Great Lakes Region
Cheektowaga, NY 14225
(716) 684-8224

Mid-Atlantic Region
Charlotte, NC 28273
(704) 588-9920

Midwest Region
St. Louis, MO 63111
(314) 256-0833

Gulf Coast Region
Pasadena, TX 77503
(281) 930-7777