

Eaglewash I

Eaglewash I Pressure Washer Hose



Application: For use on pressure washer machines with working pressures up to 4000 psi and temperatures up to 310°F.

Tube: Synthetic rubber, resistant against cold and hot water with usual cleaning agents.

Reinforcement: One braid of high tensile steel wire.

Cover: Abrasion and ozone resistant synthetic rubber, wrapped or smooth.

Temperature: 14°F to 310°F

Packaging: 500 ft 2 piece reels or cut-to-length coils

Branding: 3/8" EAGLEWASH 4001 PRESSURE WASHER HOSE PSI / 310 DEG F #Q##

Couplings: Hydraulic 100R1 type crimped to fitting manufacturer specifications

Colors: Blue, Gray, Black

Features:

- Available in bulk, 50 ft., 100 ft., and custom lengths
- Lightweight and easy to handle
- A unique cover compound gives JGB Eaglewash I hoses the durability and flexibility to handle abrasion and normal cleaning chemicals used in the wash industry.

Part #			Nom. ID	OD	Bend Radius	Min Burst	Max. Oper. Pressure	Weight
Black	Blue	Grey	in	in	in	psi	psi	lbs/ft
168-6006-30011	168-0066-40001	168-0067-40001	3/8	.59	2.6	12,183	4061	.148



Liverpool Location ISO 9001:2015 Certified QMS by Intertek

Download the JGB® Mobile App



Click for directions:

New England Region
Liverpool, NY 13088
(315) 451-2770

Great Lakes Region
Cheektowaga, NY 14225
(716) 684-8224

Mid-Atlantic Region
Charlotte, NC 28273
(704) 588-9920

Midwest Region
St. Louis, MO 63111
(314) 256-0833

Gulf Coast Region
Pasadena, TX 77503
(281) 930-7777

Connect with us:



www.jgbhose.com