

*EnviroDuct®

This product is not recommended for aircraft ground support applications.

1399-SD/1899-HD *Insulated and Non-Insulated EnviroDuct®*

Application: Air conditioning, ambient air movement, dehumidification
Construction: PVC/Polyester Substrate with Steel Wire Helix, Sewn Construction
Weight: 1399-SD: 13 oz./yd.² (441 g/m²), 1899-HD: 18 oz./yd.² (610 g/m²)
Temperature: -20° to 180° F (-29° to 82° C)



1399-SD/1899-HD

Pitch

Diameters

Standard Pitch:	3" (7.5 cm) 4" (10 cm)	6" & 7" (150 & 200 mm) 8" (200 mm) or Larger
Expanded Pitch:	7" (18 cm)	12" (300 mm) or Larger

Wire: Hard-Drawn Steel
Inside Diameter: 6" - 36" (150 - 900 mm)
Length: 15', 25' (4.5, 7.5 m)
Color: Black, Blue, Desert Tan, Green, Olive Drab, Red, White, Yellow
Optional Wearstrip: Heavy-Duty Extruded PVC
Optional End Finishes: Belt Cuff, Soft Cuff, Wire Rope Coupling

High Polish

Application: Air conditioning, ambient air movement, dehumidification, drying, general purpose blower hose
Construction: PVC/Polyester Substrate with Steel Wire Helix, Sewn Construction
Weight: 14 oz./yd.² (475 g/m²)
Temperature: -20° to 180° F (-29° to 82° C)



High Polish

Pitch

Diameters

Standard Pitch:	3" (7.5 cm) 4" (10 cm)	6" & 7" (150 & 200 mm) 8" (200 mm) & Larger Diameters
Expanded Pitch:	7" (18 cm)	12" (300 mm) and Larger Diameters

Wire: Hard-Drawn Steel
Inside Diameter: 6" - 36" (150 - 900 mm)
Length: 15', 25' (4.5, 7.5 m)
Color: White
Optional Wearstrip: Heavy-Duty Extruded PVC
Optional End Finishes: Belt Cuff, Soft Cuff, Wire Rope Coupling, Screw Clamp Cuff, Zipper Cuff

15WK

Insulated and Non-Insulated EnviroDuct®

Application: Portable heater ducting with moderately high heat content
Construction: Thermoplastic Elastomer with Warp Knit Backer, Steel Wire Helix, Sewn Construction
Weight: 15 oz./yd.² (509 g/m²)
Temperature: -65° to 350° F (-54° to 177° C) intermittent



15WK

Pitch

Diameters

Standard Pitch:	3" (7.5 cm) 4" (10 cm)	6" & 7" (150 & 200 mm) 8" (200 mm) or Larger
Expanded Pitch:	7" (18 cm)	12" (300 mm) or Larger

Wire: Hard-Drawn Steel
Inside Diameter: 6" - 36" (150 - 900 mm) Larger diameters available upon request.
Length: 15', 25' (4.5, 7.5 m)
Color: Black, Desert Tan, Olive Drab, White, Yellow
Optional Wearstrip: Heavy-Duty Extruded PVC
Optional End Finishes: Pinlock Coupling, Belt Cuff, Wire Rope Coupling, Soft Cuff

* EnviroDuct® is a registered trademark of ABC Industries, Inc.

Liverpool Location ISO 9001:2015 Certified QMS by Intertek



WARNING: Cancer and Reproductive Harm - www.P65Warnings.ca.gov

Download the JGB® Mobile App



Click for directions:

New England Region
 Liverpool, NY 13088
 (315) 451-2770

Great Lakes Region
 Cheektowaga, NY 14225
 (716) 684-8224

Mid-Atlantic Region
 Charlotte, NC 28273
 (704) 588-9920

Midwest Region
 St. Louis, MO 63111
 (314) 256-0833

Gulf Coast Region
 Pasadena, TX 77503
 (281) 930-7777

Connect with us:



www.jgbhose.com