

FLOPPYGUARD™ Hose



STRIPWOUND METAL HOSE

FloppyGuard™ (Interlocked) is Hose Master's line of floppy interlocked metal hose. Constructed from T304 or T316 stainless steel, this product offers flexibility, strength, durability, and crush resistance. FloppyGuard™ is available in sizes from 3/16" – 12" ID.

SB xx _____ xxxx

Material Code

Materials:

SS – T304 Stainless Steel
16 – T316 Stainless Steel

Nominal Inside Diameter (in.)	Part Number	Standard Material Thickness**	Min. Bend Radius (in.)	Weight Per Foot (lbs.)
44271	SB08_0018	0.008	1.1	0.05
44200	SB08_0025	0.008	1.4	0.05
44332	SB08_0031	0.008	1.7	0.06
44263	SB10_0037	0.01	2.2	0.11
44393	SB10_0043	0.01	2.5	0.12
44198	SB12_0050	0.012	2.8	0.17
44455	SB12_0056	0.012	3.5	0.19
44324	SB12_0062	0.012	3.8	0.21
44259	SB12_0075	0.012	4.9	0.27
44385	SB12_0087	0.012	5.7	0.29
1	SB12_0100	0.012	6.5	0.31
1.125	SB12_0112	0.012	7.1	0.38
1.25	SB12_0125	0.012	7.7	0.41
1.375	SB12_0137	0.012	8.3	0.47
1.5	SB12_0150	0.012	8.8	0.51
1.625	SB12_0162	0.012	9.1	0.53
1.75	SB12_0175	0.012	9.4	0.55
1.875	SB12_0187	0.012	9.7	0.59
2	SB12_0200	0.012	9.9	0.7
3	SB15_0300	0.015	12	1.4
4	SB15_0400	0.015	16	1.9
5	SB15_0500	0.015	19	2.2
6	SB15_0600	0.015	23	2.7
7	SB15_0700	0.015	27	3.1
8	SB15_0800	0.015	30	3.5
10	SB15_1000	0.015	38	4.4
12	SB18_1200	0.018	45	6.2

**Fractional sizes and other material gauges may be available. Please consult factory



Liverpool Location ISO 9001:2015 Certified QMS by Intertek

Download the JGB® Mobile App



Connect with us:



www.jgbhose.com

Click for directions:

New England Region
Liverpool, NY 13088
(315) 451-2770

Great Lakes Region
Cheektowaga, NY 14225
(716) 684-8224

Mid-Atlantic Region
Charlotte, NC 28273
(704) 588-9920

Midwest Region
St. Louis, MO 63111
(314) 256-0833

Gulf Coast Region
Pasadena, TX 77503
(281) 930-7777