

Goldendrill 3000

Rotary Drilling/Vibrator Hose



Application: Flexible connection between standpipe and swivel (rotary drilling) or between pump and standpipe (rotary vibrator) for pumping mud at very high pressure in oil drilling and exploration works

Tube: Oil and abrasion resistant synthetic rubber

Cover: Black synthetic rubber with high abrasion, weather and heat resistance

Reinforcement: Four high tensile steel wire spirals

Temperature: -4°F to 212°F (Continuous Service Range)*

Fluids: Water and mud, mineral oils, glycols and polyglycols, mineral oils in aqueous emulsion

Specs: API 7K FSL 1 and ISO14693 qualification criteria

Approvals: MSHA

* Min. hose temperature resistance according to ISO 10619-2 method:

- Tube (internal mud): -50°F (-46°C)
- Cover (environment): -67°F (-55°C)

Features:

- Highly robust and flexible, compact spiral hose structure
- Extremely high ozone, weather and abrasion resistant hose cover
- Flame retardant (MSHA) and antistatic properties
- Coupling solution uses a distinctive double skive, crimped-on hose fitting, creating a highly robust, safe connection

PART #	SIZE			R.O.D.		O.D.		MAX W.P.		BURST		MIN. BEND		WEIGHT		FITTINGS
	DN	dash	inch	mm	inch	mm	inch	bar	psi	bar	psi	mm	inch	g/m	lb/ft	Std1
H11001076	76	- 48	3	87.8	3.46	91.8	3.61	207	3000	517	7490	700	27.56	5200	3.49	IP+M01500-48



Liverpool Location ISO 9001:2015 Certified QMS by Intertek

Download the JGB® Mobile App



Click for directions:

New England Region
Liverpool, NY 13088
(315) 451-2770

Great Lakes Region
Cheektowaga, NY 14225
(716) 684-8224

Mid-Atlantic Region
Charlotte, NC 28273
(704) 588-9920

Midwest Region
St. Louis, MO 63111
(314) 256-0833

Gulf Coast Region
Pasadena, TX 77503
(281) 930-7777

Connect with us:



www.jgbhose.com