JGB Enterprises



Fittings & Accessories

Hammer Unions

100 Series Forged Steel

Used on low pressure manifolds and lines and in applications running air, water, oil or gas up to 1,000 PSI NSCWP (non-shock cold working pressure).



Size (in)	Configuration	NSCWP	Part #
2	threaded 100 series	1000	039-HU100200
2	buttweld 100 series	1000	039-HU100200BW*
2 1/2	threaded 100 series	1000	039-HU100250
3	threaded 100 series	1000	039-HU100300
4	threaded 100 series	1000	039-HU100400
4	buttweld 100 series	1000	039-HU100400BW*
6	threaded 100 series	1000	039-HU100600
8	threaded 100 series	1000	039-HU100800

^{*} buttweld ends are schedule 80

200 Series Forged Steel

Used in general service applications running air, water, oil or gas up to 2,000 PSI NSCWP (non-shock cold working pressure).



Size (in)	Configuration	NSCWP	Part #
1	threaded 200 series	2000	039-HU200100I
1 1/2	threaded 200 series	2000	039-HU200150
2	threaded 200 series	2000	039-HU200200
2	buttweld 200 series	2000	039-HU200200BW*
2 1/2	threaded 200 series	2000	039-HU200250
3	threaded 200 series	2000	039-HU200300
4	threaded 200 series	2000	039-HU200400
6	threaded 200 series	2000	039-HU200600

^{*} buttweld ends are schedule 80

Download the JGB® Mobile App









KCNs & Water Shanks



1502 Series Forged Steel

For use in extreme high pressure applications running air, water, oil, gas or mud up to 15,000 PSI NSCWP (non-shock cold working pressure)



Size (in)	Configuration	NSCWP	Part #
2	threaded 1502 series	15000	039-HU1502200

206 Series **Forged Steel**

O-ring mounted sub provides excellent sealing properties, runs air, water, oil or gas up to 2,000 PSI NSCWP (non-shock cold working pressure).



Size (in)	Configuration	NSCWP	Part #
1	threaded 206 series	2000	039-HU206100
1 1/2	threaded 206 series	2000	039-HU206150
2	threaded 206 series	2000	039-HU206200
2 1/2	threaded 206 series	2000	039-HU206250
3	threaded 206 series	2000	039-HU206300
4	threaded 206 series	2000	039-HU206400
6	threaded 206 series	2000	039-HU206600

206 Series **Forged Steel**

Features:

- · one-piece design
- interchangeable with current fittings
- · durable and safe with reliable hose retention
- · no leak path as experienced with two-piece threaded systems



Size (in)	Configuration	NSCWP	Part #
4	threaded 200 series	2000	039-HUMF206400CS



Liverpool Location ISO 9001:2015 Certified QMS by Intertek

Download the JGB® Mobile App





