

LNG Bunkering Hose

Metal Hose

Hose for LNG Bunkering

Liquefied Natural Gas (LNG) systems present special challenges during bunkering/fueling activities. LNG is typically transferred at -162 degrees C (-260 degrees F), well beyond the low-temperature limits of many hose materials. Hose Master offers specially designed corrugated metal hose assemblies that can handle the extreme temperatures and harsh environments encountered when transferring LNG. Whether shore-based systems or on-board components, Hose Master provides certified solutions for LNG bunkering operations.

During LNG transfer, ice builds up on the exterior of the assembly, which can damage bunkering hoses if improperly designed. Additionally, LNG is subject to phase changes (liquid to gas, gas to liquid), resulting in pressure and temperature variations that can cause less rugged hoses to deform or collapse. Our special braid construction and proprietary fabrication techniques ensure that the assembly can hold up under the toughest conditions.



Features:

- 316L offers excellent low-temperature resistance at cryogenic temperatures well below -260° F
- Phase changes of LNG during transfer can result in elevated pressures or full vacuum conditions. Annular stainless steel corrugations provide tremendous hoop strength to resist both conditions
- Special braid construction helps prevent ice buildup from damaging the core hose and braid
- Fully-welded high quality fabrication: All manufacturing completed in an ISO compliant facility with welding certified to our ASME IX cryogenic specific weld procedures requiring fully purged welds
- ABS Product Type Approved: Complies with Steel Vessel Rules 2019, Part 5C, Chapter 8: Vessels Intended to Carry Liquefied Gases in Bulk (5C-8-5/11.7)
- Available conformance to ASTM F3312/F3312M - 18 Standard Practice for Liquefied Natural Gas (LNG) Bunkering Hose Transfer Assembly
- Available conformance to Coast Guard Requirements

Benefits:

- **Reliability:** Proprietary manufacturing and fabrication methods ensure maximum service life in demanding environments
- **Safety:** 100% stainless steel construction offers the best resistance to extreme temperatures encountered during LNG transfer, and is fire-resistant
- **Versatility:** Able to accommodate vapor and liquid media phases because stainless steel construction eliminates media permeation issues
- **Durability:** Quality fabrication by ASME B&PV Code Section IX certified welders ensure positive fitting retention and provides maximum resistance to corrosion and metal fatigue
- **Ease of Use:** Superior flexibility combined with a compact end fitting configuration facilitates handling while connecting and disconnecting hoses, reducing worker fatigue



Liverpool Location ISO 9001:2015 Certified QMS by Intertek

Click for directions:

New England Region
Liverpool, NY 13088
(315) 451-2770

Great Lakes Region
Cheektowaga, NY 14225
(716) 684-8224

Mid-Atlantic Region
Charlotte, NC 28273
(704) 588-9920

Midwest Region
St. Louis, MO 63111
(314) 256-0833

Gulf Coast Region
Pasadena, TX 77503
(281) 930-7777

Download the JGB® Mobile App



Connect with us:



www.jgbhose.com