

J-FLEX® 4SH XFLEX



J-FLEX XFlex Hydraulic Hose

Application: Hydraulic systems with high peak pressures and arduous operating conditions needing extremely high flexibility. Due to its extreme flexibility, XFlex is perfect for use in extraordinarily tight positions.

Tube: Oil-resistant synthetic rubber

Reinforcement: 4 braids of high tensile steel spirals

Cover: Black MSHA, made of synthetic rubber, resistant to oil and weather conditions

Temperature: -40°F to +248°F (257°F intermittent)

Branding: J-FLEX® DIN EN 856 4SH XFlex 6150 PSI/424 BAR MAX WP MSHA

Couplings: Contact JGB for proper fitting recommendation and coupling procedure.

Part #	ID	OD	Bend Radius	WP	Burst Pressure	Weight
	in	in	in	psi	psi	lbs/ft
182-4020-5100IM	1-1/4	1.78	14.0	5,075	20,300	1.68
182-4024-4200IM	1-1/2	2.08	20.0	4,205	16,820	2.08
182-4032-3625IM	2	2.66	25.0	3,625	14,790	2.92



Liverpool Location ISO 9001:2015 Certified QMS by Intertek

Click for directions:

New England Region
Liverpool, NY 13088
(315) 451-2770

Great Lakes Region
Cheektowaga, NY 14225
(716) 684-8224

Mid-Atlantic Region
Charlotte, NC 28273
(704) 588-9920

Midwest Region
St. Louis, MO 63111
(314) 256-0833

Gulf Coast Region
Pasadena, TX 77503
(281) 930-7777

Download the JGB® Mobile App



Connect with us:



www.jgbhose.com