

# J-FLEX® 17M SAE 100R17



## Medium Pressure Hydraulic Hose

**Application:** Designed for medium pressure hydraulic systems in industry and agriculture

**Tube:** Synthetic rubber, resistant against hydraulic fluids

**Reinforcement:** One braid DN 06 – DN 12 and two braids DN 16 – DN 25 of high tensile steel wire

**Cover:** Abrasion and ozone resistant synthetic rubber. Note: various covers available.

**Temperature:** -40 °F to 212 °F (max 248 °F intermittent)

**Branding:** J-FLEX® 17 SAE 100R17

Part #	ID	OD	WP	Burst	Bend Radius	Weight
	in	in	psi	psi	in	lbs/ft
171-1004-3000I	1/4	0.49	3000	12000	2.0	0.11
171-1006-3000I	3/8	0.63	3000	12000	2.5	0.18
171-1008-3000I	1/2	0.77	3000	12000	3.5	0.26
172-1012-3000	3/4	1.08	3000	12000	4.7	0.51
172-1016-3000	1	1.43	3000	12000	5.9	0.85



Liverpool Location ISO 9001:2015 Certified QMS by Intertek

Click for directions:

**New England Region**  
Liverpool, NY 13088  
(315) 451-2770

**Great Lakes Region**  
Cheektowaga, NY 14225  
(716) 684-8224

**Mid-Atlantic Region**  
Charlotte, NC 28273  
(704) 588-9920

**Midwest Region**  
St. Louis, MO 63111  
(314) 256-0833

**Gulf Coast Region**  
Pasadena, TX 77503  
(281) 930-7777

Download the JGB® Mobile App



Connect with us:



[www.jgbhose.com](http://www.jgbhose.com)