

JGB Enterprises




CONCRETE PUMPING & PLACEMENT HOSE PRODUCTS



JGB® Enterprises is proud to present Eaglecrete® Concrete Placement hoses and accessories. These material handling hoses and accessories are designed and manufactured to stand up to the most abrasive applications, and materials from sand, shot, dry cement, gravel, seed, lime, animal feed, and even mild chemicals, agricultural sprays, and hot air.

Contact our Sales Department for more Info at 315-451-2770



EAGLECRETE® 1233

1233 psi plaster, grout & shotcrete handling hose.

Part #	ID	OD	Plies	WP	Burst	Weight
	in	in		psi	psi	lbs/ft
060-0242-1000	1 ½	2.20	4	1233	2465	1.07
060-0322-0800	2	2.76	4	1233	2465	1.43
060-0402-1000	2 ½	3.31	4	1233	2465	1.76
060-0482-1000	3	4.01	6	1233	2465	2.72
060-0562-1000	3 ½	4.64	6	1233	2465	3.51
060-0642-1000	4	5.12	6	1233	2465	4.90

Tube: Black Conductive Natural Rubber
Abrasion loss Value: According to DIN 53516 ≤ 60 mm³

Cover: NR/SBR Blend

Reinforcement: Spiral Wire

Couplings: Heavy Duty, Vic, NPT and Metric
Mtl Hardness: Rockwell C Scale 60 +/- 2

Temperature: -40°F to 180°F



EAGLECRETE® 1300

1300 psi cement & concrete material handling hose.

Part #	ID	OD	Plies	WP	Burst	Weight
	in	in		psi	psi	lbs/ft
060-0322-1300	2	2.76	2	1300	2900	2.04
060-0402-1300	2 ½	3.46	4	1300	2600	3.01
060-0482-1300	3	4.02	4	1300	2600	3.67
060-4692-1300	4	5.12	4	1300	2600	5.69
060-4802-1300	5	6.10	4	1300	2600	6.47

Tube: Black Conductive Natural Rubber
Abrasion loss Value: According to DIN 53516 ≤ 60 mm³


Cover: NR/SBR Blend

Reinforcement: Spiral Wire

Couplings: Heavy Duty, Vic, NPT and Metric
Mtl Hardness: Rockwell C Scale 60 +/- 2

Temperature: -40°F to 180°F

* See Reverse for Accessories





Concrete Pump Clamps

Heavy-duty, Vic, or Metric couplings for concrete pumping systems.
Size Range: from 1-1/2" to 5"

Concrete Placement Elbows

Sold in various combinations. 90° and 45° elbows available.
Size Range: from 2" to 5"



Gaskets for concrete clamps

Gaskets designed to be used with concrete pump clamps.
Size Range: from 1-1/2" to 5"

Steel Reducers for Concrete Placement

Sold in various sizes and lengths. Available with heavy-duty or metric ends.
Size Range: from 6" down to 1-1/2"



Boom & Deck Pipe for Concrete Placement

Sold in various sizes and lengths.

Slick Line Pipe for Concrete Placement

Sold in various sizes and lengths.
Size Range: from 2" to 5"



Concrete Clean Out Balls

Sponge Balls for cleaning Soft, medium, or hard available
Size Range: from 2" to 6"

Concrete Weld-On End

Weld-On Ends for cement & concrete hose
Size Range: from 2" to 6"



Liverpool Location ISO 9001:2015 Certified QMS by Intertek

Download the JGB® Mobile App



Click for directions:

JGB® Headquarters
Liverpool, NY 13088
(315) 451-2770

Buffalo Branch
Cheektowaga, NY 14225
(716) 684-8224

Southeast Hub
Charlotte, NC 28273
(704) 588-9920

St. Louis Branch
St. Louis, MO 63111
(314) 256-0833

Williston Branch
Williston, ND 58801
(701) 774-2195

Houston Branch
Pasadena, TX 77503
(281) 930-7777

Connect with us:



www.jgbhose.com