

Liquid Waste Management Hose & Accessories

Eagle Pump HD 150



Natural & Synthetic black rubber blended suction hose. Reinforced with a textile & steel helix wire. Temperature range: -22°F to 185°F.

***Available in bulk & custom lengths/configurations.**
***Standard assemblies include Aluminum CxE Camlocks.**

Suction Hose Assembly

ID	WP	Price			Bulk
		25'	50'	100'	
1-1/2"	150	000	000	000	
2"	150	000	000	000	
2-1/2"	150	000	000	000	
3"	150	000	000	000	
4"	150	000	000	000	
6"	150	000	000	000	

Eagle Honeybee



Ultra Lightweight & Flexible plastic suction hose. Yellow and Black "Honeybee" polyethelene reinforcement with vinyl cuffed ends. Rated for full vacuum with a temperature range of -40°F to 150°F.

***Available in bulk & Custom lengths/configurations.**
***Standard assemblies include Aluminum CxE Camlocks.**

Suction Hose Assembly

ID	WP	Price								Bulk
		10'	20'	25'	30'	40'	50'	60'	100'	
2	15	000	000	000	000	000	000	000	000	000
3	7	000	000	000	000	000	000	000	000	000

Eagle EPDM



Most popular all-weather suction hose. Green & Black EPDM reinforced with a green polyethylene helix for abrasion resistance. Can be used for full vacuum service. Temperature range -40°F to 140°F.

***Available in bulk & Custom lengths/configurations.**
***Standard assemblies include Aluminum CxE Camlocks.**

Suction Hose Assembly

ID	WP	Price				Bulk
		25'	30'	35'	100'	
1	50	000	000	000	000	
1-1/4	50	000	000	000	000	
1-1/2	50	000	000	000	000	
2	50	000	000	000	000	
3	45	000	000	000	000	
4"	38 psi	000	000	000	000	

Eagle Green/Clear PVC



Designed for standard-duty water suction & transfer service. PVC spiral helix for reinforcement supports full vacuum. Temperature range: -10°F to 140°F.

***Available in bulk & Custom lengths/configurations.**
***Standard assemblies include Aluminum CxE Camlocks.**

Suction Hose Assembly

ID	WP	Price					Bulk
		25'	50'	30'	35'	100'	
1-1/2	70	000	000	000	000	000	
2	65	000	000	000	000	000	
2-1/2	50	000	000	000	000	000	
3	50	000	000	000	000	000	
4	45	000	000	000	000	000	
6	30	000	000	000	000	000	
8	30	000	000	000	000	000	

Eagle Tank



Reinforced Nitrile Tank truck hose for applications requiring maximum oil resistance. Eagle Tank is rated for full vacuum, and the 2" & 2-1/2" meet SAE 100R4 Specs. Temperature range: -40°F to 180°F.

***Available in bulk & Custom lengths/configurations.**
***Standard assemblies include Aluminum CxE Camlocks.**

Suction Hose Assembly

ID	WP	Price			Bulk
		25'	50'	100'	
1-1/2	150	000	000	000	
2	150	000	000	000	
2-1/2	150	000	000	000	
3	150	000	000	000	
4	150	000	000	000	
6	150	000	000	000	
8	150	000	000	000	

The Perfect Garden Hose



Ultra-Lightweight, Ultra-Flexible (even in extreme cold), kink PROOF, 5/8" Water wash-down hose. Standard brass GHT couplings. Temperature range: -20°F to 158°F.

***25' Colors: Blue**
***50' Colors: Blue, Green, Red, Beige, Gray, & Pink**
***100' Colors: Blue & Green**

Garden Hose Assembly

ID	WP	Price		
		25'	50'	100'
5/8	100	000	000	000

Valves



Brass Valves

Multi-purpose shut-off valves for residential and light commercial applications.

Standard ID's: 2", 3", & 4"

***Additional sizes & types available**

Hose Fittings



Polypropylene Valves

For use with hot corrosive liquids, chemical processing.

Standard ID's: 1-1/2", 2", 3", & 4"

***Additional sizes & types available**

Aluminum & Poly Cams



Aluminum Cam & Groove

Standard multi-purpose Cam Lock Quick Connects for hoses.

Standard ID's: 1-1/2" through 8"

***Additional sizes & types available**

Hose Fittings



Polypropylene Cam & Groove

Cam Lock Quick Connects for use with hot corrosive liquids, chemical processing.

Standard ID's: 1-1/2" through 4"

***Additional sizes & types available**

Water Shanks



Hose Shank Couplings

Aluminum couplers with brass swivel pin lug.

Standard ID's: 1-1/2" through 6"

***Additional sizes available**

Hose Fittings



King Combination Nipples (KCN)

Combination Nipples are used in a variety of fluid applications.

Standard ID's: 1/2" through 8"

***Additional sizes & types available**

Strainers & Sight Glasses



Hose Strainers

Filters out large damaging debris for equipment protection.

Standard ID's: 1-1/2" through 8"

***Additional sizes & types available**

Hose Accessories



Sight Glass

Easily monitor flow and the collection of debris fluids.

Standard ID's: 2" through 4"

***Additional sizes & types available**

Punch Lock Clamps & Gaskets



Punch Lock, Worm Gear, T-Bolt, Spiral, & More

Couple your low pressure assemblies yourself with our multitude of hose clamp styles available.

***Additional sizes & types available**

Hose Accessories




Gaskets

Eliminate leaks and prevent corrosion with JGB's Buna Gaskets.

Standard Sizes: 1/2" through 6"

***Additional sizes & types available**



**WARNING: Cancer and
- Reproductive Harm**
www.P65Warnings.ca.gov

Liverpool Location ISO 9001:2015 Certified QMS by Intertek



JGB Headquarters
Liverpool, NY 13088
(315) 451-2770

Buffalo Branch
Cheektowaga, NY 14225
(716) 684-8224

Southeast Hub
Charlotte, NC 28273
(704) 588-9920

St. Louis Branch
St. Louis, MO 63111
(314) 256-0833

Williston Branch
Williston, ND 58801
(701) 774-2195

Houston Branch
Pasadena, TX 77503
(281) 930-7777