


## T-REX SB<sup>®</sup> Hose

## Metal Hose



### STRIPWOUND METAL HOSE

T-Rex SB™ (Smoothbore) is a torque-resistant smoothbore metal hose with enhanced sealability. T-Rex™ provides optimum resistance to twisting, unwinding, or metal strip flare up when cut.

RX Armor Material Armor Thickness Liner Material

#### Applications:

- Dry bulk pneumatic conveying
- Material handling
- Pellet transfer
- Bulk unloading

#### Materials:

- GS - Galvanized Steel
- S - T304 Stainless Steel
- 6 - T316 Stainless Steel
- 2 - T201 Stainless Steel

#### Armor Strips:

- 15 – Light Weight
- 18 – Medium Weight

#### Liner Materials (Im):

- S – Stainless Steel
- C – Carbon Steel
- 4 – Magnetic Liner\*

Example: RXS15S has an armor made of T304 stainless steel strip .015" thick, and a stainless steel liner.

Inside Diameter (in.)	RX_15__ (G,S,6,2) (S,C,4)		RX_18__ (G,S,6) (S,C,4)		RXS18S25*	
	Wt. Per Ft. (lbs.)	Min. Bend Radius (in.)	Wt. Per Ft. (lbs.)	Min. Bend Radius (in.)	Wt. Per Ft. (lbs.)	Min. Bend Radius (in.)
	4	3	17	3.4	18	4.1
4.5	3.4	19	3.8	21	4.11.5	26
5	3.7	21	4.2	23	5	29
6	4.5	25	5	27	6	34
7	5.2	29	5.8	32	6.9	40
8	5.9	33	6.6	36	7.9	45
9	6.6	37	7.4	40	8.8	51
10	7.4	40	8.2	45	9.7	56
11			9	49	10.7	62
12			9.8	53	11.7	67
13			10.6	58	12.7	73
14			11.4	62	13.6	78
15			12.2	66	14.6	84
16			13.1	71	15.5	89

\*RXS18S25 is constructed with a stainless steel .018 armor and a .025 stainless liner



Liverpool Location ISO 9001:2015 Certified QMS by Intertek

Click for directions:

New England Region  
Liverpool, NY 13088  
(315) 451-2770

Great Lakes Region  
Cheektowaga, NY 14225  
(716) 684-8224

Mid-Atlantic Region  
Charlotte, NC 28273  
(704) 588-9920

Midwest Region  
St. Louis, MO 63111  
(314) 256-0833

Gulf Coast Region  
Pasadena, TX 77503  
(281) 930-7777

Download the JGB<sup>®</sup> Mobile App



Connect with us:



www.jgbhose.com