

# TAR & ASPHALT Hose



## STRIPWOUND METAL HOSE

**Tar and Asphalt** hose is Hose Master's heavy-weight interlocked metal hose. Constructed from a single strip of galvanized steel with Hose Master's proprietary packing, this hose is used for transferring high-temperature, viscous fluids. Tar & Asphalt hose is leak-resistant and handles maximum suction. It is design-tested to 100 psi and has a temperature range of -40° F. to 500° F.

Explanation of Tar & Asphalt Part Numbers:

TA \_\_\_\_\_  
*Thickness Code    Material Code*

**Strip Thicknesses:**  
 25 – Heavy Weight  
 30 – Extra Heavy Weight

**Material Codes:**  
 SS – 201 Stainless Steel  
 GS – Galvanized Steel

Inside Diameter (in.)	Min. Bend Radius (in.)	25-Heavy Weight, 201 Stainless Steel	30-Extra Heavy Weight, Galvanized Steel
		Wt. Per Ft. (lbs.)	Wt. Per Ft. (lbs.)
2	12	1.9	2.2
2.5	15	2.4	2.8
3	17	2.7	3.2
4	22	3.6	4.2

### Notes:

25 – Heavy Weight Strip is only available in 201 Stainless Steel

30 – Extra Heavy Weight Strip is only available in Galvanized Steel

Other diameters are available upon request

Minimum bend radius is measured from the centerline of the hose



Download the JGB® Mobile App



Connect with us:



[www.jgbhose.com](http://www.jgbhose.com)

Liverpool Location ISO 9001:2015 Certified QMS by Intertek

Click for directions:

**New England Region**  
 Liverpool, NY 13088  
 (315) 451-2770

**Great Lakes Region**  
 Cheektowaga, NY 14225  
 (716) 684-8224

**Mid-Atlantic Region**  
 Charlotte, NC 28273  
 (704) 588-9920

**Midwest Region**  
 St. Louis, MO 63111  
 (314) 256-0833

**Gulf Coast Region**  
 Pasadena, TX 77503  
 (281) 930-7777