

Thunderbolt®

Water

Thunderbolt® Pressure Washer Hose



Application: Designed for use on either combination machines or pressure washer machines.

Tube: Black, heat resistant synthetic rubber

Reinforcement: One wire braid

Cover: Black heat and oil resistant synthetic rubber RMA class B (pin pricked)

Temperature: Handles up to 325°F (163°C) steam at 350 psi with a safety factor in excess of 10 to 1. Handles up to 250°F (121°C) water at 3000 psi with a 4 to 1 safety factor

Packaging: 300 ft reels, multiples of 50 ft max

Branding: 3/8" THUNDERBOLT® COMBO 3000 PSI / 250°F - 350 PSI / 325°F

Couplings: Recommend testing with hydraulic 100R1 over the wire (Skive hose) fittings crimped to the fitting manufacturer specifications. Compatibility with different over the wire fittings should be tested prior to use.

Features:

- Abrasion-resistant cover prevents wear due to dragging.
- Chemical-resistant inside and out, to handle most of the detergents and chemicals used in industry today.
- High-pressure, one-wire braid takes up to 3000 psi - meeting or exceeding specs for virtually every pressure washer available.
- Ensures worry-free installation in hot, cold or combo applications.
- Available in 50 ft. lengths.

Part #	Nom. ID	Nom. OD	Bend Radius	Min. Burst	Max. Oper. Pressure		Weight
	in	in	in	psi	psi@ 250°F	psi@ 325°F	lbs/ft
171-9006-3000	3/8	.690	2.5	12,000	3000	350	.21



Liverpool Location ISO 9001:2015 Certified QMS by Intertek

Download the JGB® Mobile App



Click for directions:

New England Region
Liverpool, NY 13088
(315) 451-2770

Great Lakes Region
Cheektowaga, NY 14225
(716) 684-8224

Mid-Atlantic Region
Charlotte, NC 28273
(704) 588-9920

Midwest Region
St. Louis, MO 63111
(314) 256-0833

Gulf Coast Region
Pasadena, TX 77503
(281) 930-7777

Connect with us:



www.jgbhose.com