

Eagle Arctic[®] Oilfield 150 PSI

Eagle Arctic[®] Oilfield 150 PSI



For suction and discharge applications in truck and tank car transfer of gasoline, oil and other petroleum-based products with up to 50% aromatic content. For use where extreme flexibility is needed in low temperature.

- Tube:** Black conductive oil resistant Nitrile (NBR)
- Reinforcement:** High tensile textile cords and highly flexible steel helix
- Cover:** Blue corrugated - abrasion, hydrocarbon and ozone resistant
- Temperature:** -65°F to +180°F
- Branding:** EAGLE ARCTIC[®] OILFIELD 150 PSI WP
- Couplings:** Contact JGB for proper fitting recommendation and coupling procedure

Part #	ID	OD	Min Bend Radius	WP	Weight
	in	in	in	psi	lbs/ft
009-0326-0150IA	2	2.51	2	150	1.10
009-0486-0150IA	3	3.62	3	150	2.67
009-0646-0150IA	4	4.64	4	150	2.84

* Full Vacuum



Liverpool Location ISO 9001:2015 Certified QMS by Intertek

Click for directions:

New England Region
Liverpool, NY 13088
(315) 451-2770

Great Lakes Region
Cheektowaga, NY 14225
(716) 684-8224

Mid-Atlantic Region
Charlotte, NC 28273
(704) 588-9920

Midwest Region
St. Louis, MO 63111
(314) 256-0833

Gulf Coast Region
Pasadena, TX 77503
(281) 930-7777

Download the JGB[®] Mobile App



Connect with us:



www.jgbhose.com